NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

CWATER WELL REPERCEIVED

STATE OF OREGON JUL 2 8 1975

State Well No. 45/12E-15

filed with the STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from 1 within 30 days from the date of well completion.

(Please type or print)
WATER RESOURCES Defere Permit No.
SALEM, OREGON

1) OWNER:	(10) LOCATION OF WELL:		
Name Darrel C. Ashley	County Wasco Driller's well number		
Address Rt 1, Box 33-A, Wamic, Oregon	NE 12 NE 14 Section 24 T.4 S	R. 12 E.	• W.M.
The transfer of the second sec	Bearing and distance from section or subdivision	on corner	
2) TYPE OF WORK (check):	41 Saret v. Lv . 1911		
Yew Well ☑ Deepening □ Reconditioning □ Abandon □			
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ما1	
		4	.e.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		ft.
totary № Driven □ Domestic □ Industrial □ Municipal □	Static level 159 ft. below land st	urface. Date /	-16-7 5
Oug 🗌 Bored 🗎 Irrigation 🛭 Test Well 🗍 Other 🗎	Artesian pressure Ibs. per square	e inch. Date	
CASING INSTALLED: Threaded Welded Gage .250 8 "Diam. from 0 ft. to 103 ft. Gage .250 "Diam. from ft. to ft. Gage .250 PERFORATIONS: Perforated? Yes No.	(12) WELL LOG: Diameter of well be Depth drilled 250 ft. Depth of completion: Describe color, texture, grain size a and show thickness and nature of each stratum with at least one entry for each change of format position of Static Water Level and indicate principles.	eted well 245 and structure of m n and aquifer per tion. Report each ci	netrated, hange in
Type of perforator used	MATERIAL	From To	swL
	Boulders and rocks	0 55	
Size of periorations	Boulders	55 99	
perforations fromft. toft.	Rock, Grey, Hard	99 165	
perforations fromft. toft.	Rock, lavender	165 175	
perforations from ft. to ft.	Rock, red	175 190	
(7) SCREENS: Well screen installed? Yes No	Sandstone, brown	190 198	
Manufacturer's Name	Sandstone, grey	198 206	
Type Model No	Sandstone, brown	206 212	
Diam, Slot size Set from ft. to ft.	Sandstone, grey	212 239	159
Diam, Slot size Set from ft. to ft.	Rock, broken, grey	239 243	159
(8) WELL TESTS: Drawdown is amount water level is	Sand & gravel	243 250	159
Toward pelow state level		1	
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.	The second secon	1	
" "	- 5.2		
n n n	Landing to the state of the sta		
Bailor test 100 gal./min. with ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
mperature of water Depth artesian flow encounteredft.	Work starte April 31, 19 75 Complet	ed July 16	1975
(a) CONCERNATIONALON	Date well drilling machine moved off of well	July 16	19 7
(9) CONSTRUCTION: Bentonite	Drilling Machine Operator's Certification:	•	
Well seal—Material used	This well was constructed under my Materials used and information reported best knowledge and belief.	direct super above are true Date	e to my , 19
Brand name of bentonite Yellows tone	W. L. W. H. Contractor's Contiliontion		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	· · · · · · · · · · · · · · · · · · ·	
of water65 lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and be	nction and this r	eport is
Was a drive shoe used? Yes ☐ No Plugs Size: location ft.	Name Gilbert Clayton Well Drilling		
Did any strata contain unusable water? X□ Yes □ No	(Person, firm or corporation)	(Type or pri	
Type of water? Surface depth of strata 4 feet	Address Rt 1, Box 61-A, The Dal	Lies, Ore. 9	1/058
Method of sealing strata off 26 ft. seal	Similar Silver I Sin	A Common of the	
Was well gravel packed? ☐ Yes X No Size of gravel:	[Signed] (Water Well Con	pactor)	
Craval planed from # to ft.	Contractor's License No. 569 Date	July 22,	, 197