The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, NOV 2 2 1978 STATE OF OREGON
SALEM, OREGON 97310 ATER RESOURCES DEPTE type or print) 0 35 9 4

within 30 days from the Water RESOURCES DEPTE type or print) 0 35 9 4 SALEM, OREGON not write above this line) of well completion.

	· 45/17x-15-1
State	Well No. 45/12E-75-06
State	Permit No.

	· · · · · · · · · · · · · · · · · · ·			
(1) OWNER:	(10) LOCATION OF WELL:			
Name Eugene Ashley	County WASCO Driller's well number 78-36			
AddressP.O. Box 87, Wamic, OR. 97063	NW 1/4 NE 1/4 Section 15 T. 4S	R. 12E	I .	W.M.
	Bearing and distance from section or subdivisi	ion corne	r	
(2) TYPE OF WORK (check):				
New Well □ Deepening XX Reconditioning □ Abandon □		***************************************		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	æll.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	240		ft.
Rotary Driven Domestic Dindustrial Municipal D	Static level 240 ft. below land	surface.	Date 11	/2/78
Cable	Artesian pressure lbs. per squar	re inch.	Date	
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well	below cas	ing 6	11
Notiampfficable ft. to ft. Gage	Depth drilled 503 ft. Depth of completed well 500 ft.			
"Diam, from	Formation: Describe color, texture, grain size	and struc	ture of r	naterials;
ft. Gage	and show thickness and nature of each stratu with at least one entry for each change of forms	ım and a	quifer pe	netrated,
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin			
Type of perforator used N/A	MATERIAL	From	то	SWL
Size of perforations in. by in.	ORIGINAL WELL DRILLED TO 317'			
perforations fromft. toft.	AND CASED TO 300'			·
perforations from ft. to ft.	AXV CASISV IV SVV			
perforations fromft. toft.	Sand & gravel	303	317	240
	Sandstone brown soft	317	365	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Conglomerates med.	365	370	
Manufacturer's Name	Sandstone brown med.	370	382	
Type Model No	Conglomerates med.	382	391	
Diam. Slot size Set from ft.	Sandstone, yellow soft	391	430	
Diam. Slot size Set from ft. to ft.	Sandstone brown med.	430	503	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? X Yes \(\subseteq No \) Hyes, by whom? Driller				
61 107 2.5		1		
Yield: 41 gal./min. with 107 ft. drawdown after 2.5 hrs.				
	±			
	- Committee of the comm			
Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m.	<u> </u>			
7 Depth artesian flow encounteredft.	Work started 11/2 1978 Complet	ed 11		1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	11/3	<u>- </u>	1978
IN/A	Dulling Machine Operator's Continue			,
Well seal—Material used	This well was constructed under my		super	vision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information reported			
Diameter of well bore below sealin.	best knowledge and belief.	Date:	11/2	1 78
Number of sacks of cement used in well seal	[Signed] Drilling Machine Operator)	Date	+.+.14	÷ 18.7.7.
How was cement grout placed?	Drilling Machine Operator's License No.	700	*********	
			- a	
	Water Well Contractor's Certification:	,		-,
	This well was drilled under my jurisd true to the best of my knowledge and be	iction an lief	nd this r	eport is
Was a drive shoe used? \square Yes \square No Plugs Size: location ft.				. =
Did any strata contain unusable water? Yes No	Name Marinelli Drilling Co. (Person, firm or corporation)	(T y	pe or pri	at)
Type of water? depth of strata	Address P.O. Box 571, Lake Oswes	<u> </u>	9703	4
Method of sealing strata off	Isimula Van Caram	10	Q.	
Was well gravel packed? Tyes XNo Size of gravel:	[Signed] (Water Well Cont	ractor)	<i>4</i>	
Gravel placed fromft. toft.	Contractor's License No672 Date	11/2	1	., 19.78
	· · · · · · · · · · · · · · · · · · ·			