NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT ON 36 7 3 STATE OF OREGON (Please type or print)

FEB . F 1978 te Well No. 45

SP\*45656-119

(Do not write above this MeNTER RESOURCES to DEPT. No.

	SALEM, OPEGON	
(1) OWNER:	(10) LOCATION OF WELL:	
Name V. Fleischman		-01
Address RT / BIX /2	NW 14 SE 14 Section 31 T. 4S R. 14E	W.M.
MAUPIN, DR. 97037	Bearing and distance from section or subdivision corner	***************************************
(2) TYPE OF WORK (check):	1625 N. and 2260 Ft. East of SW	
New Well   Deepening   Reconditioning   Abandon	Corner Sect. 31	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 437 ft.	
Rotary XX Driven Domestic Industrial Municipal Domestic	Static level 250 ft. below land surface. Date	1/24/78
Cable	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: NONE Threaded   Welded   Welded   Threaded   Welded   Threaded   Welded   Threaded   Threaded   Welded   Threaded   Threaded	(12) WELL LOG: Diameter of well below casing 6."  Depth drilled 540 ft. Depth of completed well 540 ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure and show thickness and nature of each stratum and aquife with at least one entry for each change of formation. Report each change of formation and the structure of th	r penetrated
PERFORATIONS: Perforated? \( \text{Yes} \) Yes \( \text{Yes} \) No.	position of Static Water Level and indicate principal water-b	earing strata.
Size of perforations in. by in.	Well cased to 375', open	o SWL
perforations from ft. to ft.	to 373'	
perforations fromft. toft.	Well originally drilled	
perforations from ft. to ft.	to 400'	(250)
		1
TO SELECT INDUMES.   Tes 24m 140		00
Manufacturer's Name		37
Type Model No Diam Slot size Set from ft. to ft.		41 (250)
Diam. Slot size Set from ft. to ft.		1.8
	Sandstone (Brown) w/b 518 5	43
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? XXYes DNo If yes, by whom? Driller		
Yield: 96 gal./min. with 118 ft. drawdown after 3 hrs.		
" "		
AIR LIET PUMP TEST "		
Bailer test gal./min. with ft. drawdown after hrs.		<del>-  </del>
Artesian flow g.p.m.		
Temperature of water 59 Depth artesian flow encounteredft.	Work started 1/24 1978 Completed 1/25	19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well 1/25	19 78
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct sur	pervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are best knowledge and being.	rue to my
Diameter of well bore below sealin.	[Signed] What Machine Operator) Date 30 Jan, 1978	
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 700	
How was cement grout placed?	Drining machine Operator's License No	
	Water Well Contractor's Certification:	55 T
	This well was drilled under my jurisdiction and th	is report is
Was a drive shoe used? 🗌 Yes 📋 No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? 🔲 Yes 🔲 No	Name //ARINELU DAILLIE (Type or print)	
Type of water? depth of strata	Address P. D. BOX 571 LAKE OSLUCI, D.	- mai
Method of sealing strata off	( ) ( ) ( ) ( )	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)	
Gravel placed fromft. to ft.	Contractor's License No. 6.72. Date 34 (cm.)	1978

(USE ADDITIONAL SHEETS IF NECESSARY)