The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(1) OWNER:	(10) LOCATION OF WELL:
Name KIETH SNODGRASS	County WASCO Driller's well number
Address BOX 11 13 POUTE	N. E 14N W 14 Section 32 T. 5 S R. 16 E W.M.
MAUPIN ORE	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	G Jawar Jawar Go, ite
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Rotary Driven Domestic Cl Industrial Municipal Cl	Depth at which water was first found 106 ft.
Cable	Static level 8 7 ft. below land surface. Date MAY 26/19
	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing /
10 " Diam. from 0 ft. to 19 ft. Gage . 250 w/h	David July 1
ft. Gage	
ft. Gageft.	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Vos. Ana	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Tellolated. Tes @Mo.	
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	BLACK CLAY LOAM 0 33
perforations from ft. to ft.	BOULDERS 32 82
perforations fromft. toft.	BROWN FIRM SANDSTONE 8 22
perforations fromft. toft.	BLACK LAYA 22 96 GREV BASAIT 96 112 40
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	
Manufacturer's Name	GREY BASALT CHONKS 127 130
Type Model No.	TAIN CONGLOMERATE 130 136 89
Diam Slot size Set from ft. to ft.	BRITTLE FRACTURED
Diam Slot size Set from ft. to ft.	BASHLT 136 140 87
(8) WELL TESTS: Drawdown is amount water level is	GREY LAVA 140 15-5-
lowered below static level	
Was a pump test made? ☐ Yes ♠ No If yes, by whom?	
Yield: gal./min. with ft, drawdown after hrs.	
" " " " " " " " " " " " " " " " " " " "	
,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,	
Bailer test 40 gal./min. with O ft. drawdown after 1/2 hrs.	
Artesian flow g.p.m.	
aperature of water 57 Depth artesian flow encountered	
perature of water o / Depth artesian now encountered ft.	Work started MAY 1 1973 Completed MAY 26 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well MAY 29 19 73
Well seal-Material used RENTONITE	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	
Number of sacks of cement used in well seal sacks	[Signed] Laurence Janualegh! Date Juige 21, 1973
Number of sacks of bentonite used in well seal $\frac{3}{2}$ $\frac{100 LB}{100}$ sacks	Drilling Machine Operator's License No
Brand name of bentonite VOLCLAY	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name LAWRENCE KAWALLESKI
Did any strata contain unusable water? Yes No	(Person, ill or corporation) (Type or print)
Type of water? depth of strata	Address 741-42h MADRAS OIRE
Method of sealing strata off	[Signed] Lawrence Howaleshi
Was well gravel packed? 🛘 Yes 🕏 No Size of gravel;	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 209 Date June 21 , 1973
	10