NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WASC WATER WELL REPORD 03769

State Well No. 6/16-2 State Permit No.

STATE OF OREGON (Please type or print)

Name Hinton and Ward RECEIVE	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
	Was a pump test made? Yes X No If yes, by whom?
	Yield: gal./min. with ft. drawdown after h
(2) LOCATION OF WELL: SALEM OFFICIAL	" " "
(2) LOCATION OF WELL: SALEM OREGON	
County Wasco Driller's well number	Bailer test gal./min. with ft. drawdown after h Artesian flow 27 g.p.m. Date Dec. 14, 1960
4 4 Section 2 T. 6S R. 16E W.M.	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made? Yes 1
	(12) WELL LOG: Diameter of well below casing6in.
	Depth drilled 97 ft. Depth of completed well 97
	Formation: Describe by color, character, size of material and structure, a
	Formation: Describe by color, character, size of material and structure, as show thickness of aquifers and the kind and nature of the material in estratum penetrated, with at least one entry for each change of formatic
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	
New Well \(\) Deepening \(\) Reconditioning \(\) Abandon \(\)	Broken gravel & clay 0 1-Basalt 7-1 76
andonment, describe material and procedure in Item 12.	721
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Dense basalt1865Visicular basalt & tuff6568
Domestic Industrial Municipal Rotary Driven Cable Zotted	
Irrigation ☐ Test Well ☐ Other Dug ☐ Bored ☐	Basalt 68 97
(C) CACING INCOMETATION	Water enters well at 70° + or - 5°
(6) CASING INSTALLED: Threaded ☐ Welded ☑ 6	WARRY GUICELS WELL ST 10. + OL).
" Diam, from	
"Diam. fromft. toft. Gage	
	~
(7) PERFORATIONS: Perforated? ☐ Yes X No	
Type of perforator used	
Size of perforations in. by in.	-
perforations from ft. to ft.	
(8) SCREENS: Well screen installed? ☐ Yes 🛣 No	
Manufacturer's Name	
Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	Work started December 19 60 Completed December 19 6
	Date well drilling machine moved off of well 19
(9) CONSTRUCTION:	(13) PUMP:
Well seal-Material used in seal casing embedded in cement	Manufacturer's Name
Depth of seal	Type: H.P.
Diameter of well bore to bottom of seal in.	
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:
Was a drive shoe used? ☐ Yes ☐ No	This well was drilled under my jurisdiction and this report
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	NAME Bent Abnome
Did any strata contain unusable water? Yes X No	NAME Bert Abrams (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address P. O. Box 726, Madras, Oregon
Method of sealing strata off	Duilling Marking O
(10) WATER LEVELS:	Drilling Machine Operator's License No.
737 m.t	[Signed]
Static level Flowing ft. below land surface Date Dec, 1960	(Water Well Contractor)
Artesian pressurelbs. per square inch Date	Contractor's License No. 70 Date Dec. 14 19 6
(USE ADDITIONAL SI	HEETS IF NECESSARY)