

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy  
of this report are to be  
filed with the

# WATER WELL REPORT

STATE OF OREGON

State Well No. 6517E-21aa

STATE ENGINEER, SALEM, OREGON 97311  
within 30 days from the date  
of well completion.

*WAESC*  
*003778*

(Please type or print)

RECEIVED

State Permit No. ....

MAY 9 1978

**(1) OWNER:**

Name Roger T. Justesen  
Address Grass Valley, Oregon 97029

**(2) TYPE OF WORK (check):** reaming

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

**(3) TYPE OF WELL:**

**(4) PROPOSED USE (check):**

Rotary  Driven  Domestic  Industrial  Municipal   
Cable  Jetted  Irrigation  Test Well  Other   
Dug  Bored

**(5) CASING INSTALLED:**

10" Diam. from 0 ft. to 20 ft. Threaded  Welded  Gage .250  
....." Diam. from ..... ft. to ..... ft. Gage .....  
....." Diam. from ..... ft. to ..... ft. Gage .....

**(6) PERFORATIONS:**

Perforated?  Yes  No

Type of perforator used

Size of perforations in. by in.  
..... perforations from ..... ft. to ..... ft.  
..... perforations from ..... ft. to ..... ft.  
..... perforations from ..... ft. to ..... ft.

**(7) SCREENS:**

Well screen installed?  Yes  No

Manufacturer's Name .....  
Type ..... Model No. ....  
Diam. .... Slot size ..... Set from ..... ft. to ..... ft.  
Diam. .... Slot size ..... Set from ..... ft. to ..... ft.

**(8) WELL TESTS:**

Drawdown is amount water level is lowered below static level

Was a pump test made?  Yes  No If yes, by whom?  
Yield: gal./min. with ft. drawdown after hrs.  
air  
Batter test 600 gal./min. with 60 ft. drawdown after 1 hrs.  
Artesian flow g.p.m.

**(9) CONSTRUCTION:**

Well seal—Material used cement grout  
Well sealed from land surface to 19 ft.  
Diameter of well bore to bottom of seal 12 in.  
Diameter of well bore below seal 10 in.  
Number of sacks of cement used in well seal 4 sacks  
Number of sacks of bentonite used in well seal ..... sacks  
Brand name of bentonite .....  
Number of pounds of bentonite per 100 gallons  
of water ..... lbs./100 gals.  
Was a drive shoe used?  Yes  No Plugs ..... Size: location ..... ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? ..... depth of strata .....  
Method of sealing strata off .....  
Was well gravel packed?  Yes  No Size of gravel: .....  
Gravel placed from ..... ft. to ..... ft.

**(10) LOCATION OF WELL:**

County WASCO, OREGON Driller's well number .....  
NE 1/4 NE 1/4 Section 21 T. 6 S. R. 17 E. W.M.

Bearing and distance from section or subdivision corner

**(11) WATER LEVEL: Completed well.**

Depth at which water was first found 117 ft.  
Static level 93 ft. below land surface. Date 4-11-78  
Artesian pressure lbs. per square inch. Date

**(12) WELL LOG:**

Diameter of well below casing 10"  
Depth drilled 185 ft. Depth of completed well 185 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Reamed well to 10"	0	185	93

Work started April 3 1978 Completed April 12 1978  
Date well drilling machine moved off of well April 12 1978

**Drilling Machine Operator's Certification:**  
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] Gilbert Clayton Date April 24 1978  
(Drilling Machine Operator)  
Drilling Machine Operator's License No. 129

**Water Well Contractor's Certification:**  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name Gilbert Clayton Well Drilling  
(Person, firm or corporation) (Type or print)  
Address Rt 1, Box 61-A, The Dalles, OR 97058  
[Signed] Gilbert Clayton  
(Water Well Contractor)  
Contractor's License No. 569 Date April 24 1978