NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

(Do not write above this line) 03809

State Well No. 75/15E-18db State Permit No.

(1) OWNER: Name G. W. SWAN	(10) LOCATION OF WELL: County WAS (7) Driller's well number
Address STAR ROUTE BOX3 MAUPIN CESE.	Harrie P. F.
97037	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	7
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	7.2
Domestic Industrial Municipal	
Dug	Static level 117 ft. below land surface. Date Joly 2/ Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded Welded Go. "Diam. from Go. ft. to Z. ft. Gage 257" "Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing 10 in Depth drilled 207 ft. Depth of completed well 207 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? Yes ONO.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	5ANDY SOIL 026
perforations from	BROKEN BLACK BASALT 24 6
perforations from ft. to ft.	BLACK BASALT 6 103
	CONGLOMORATE 122 170
(7) SCREENS: Well screen installed? Yes Ono	RHVOLITE YELLOW 170 174
Manufacturer's Name	LAVA 174 190
Type	BLACK BASALT 190 207
Diam. Slot size Set from ft. ft. Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Fig. D	RECEIVED
Yield: 580 gal./min. with 70 ft. drawdown after 5 hrs.	AUG 1 3 1980
Yield: 5 8 2 gal./min. with 10 ft. drawdown after 5 hrs.	
" " " " " " " " " " " " " " " " " " " "	WATER RESOURCES DEPT
	SALEM, OREGON
fer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started MAY 12 1980 Completed Je L Y 21 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well JULY 22 1980
Well seal—Material used CFMFKT Well sealed from land surface to 19	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Lawrence Towalesh Datoling, 10,19 80
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
How was cement grout placed? EROUT PUMP	Drilling Machine Operator's License No
4.37	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name LANRENCE KOWALESKI
Did any strata contain unusable water? Type of water?	(Person, firm or corporation) (Type or print) Address 74/54/26: MAD 12/25 (OB)
Type of water? depth of strata Method of sealing strata off	Address 741-426 MADIANS OBT
	[Signed] Luciven Lowaleshi
	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 209 Date Aug 10 , 1980