## STATE OF OREGON

RECEIVED

JUN 20 1989

STATE OF OREGON WATER WELL REPORT JUL 2 0 1989 WATER B	003874	<u> 15e/ 9 a</u>	26
(as required by ORS 537.765)  WATER RESOURCES DEPTSTART CARD) # 7134  (1) OWNER: WATER WIRDLINGES DEPTSTART CARD) # 7134  (2) OWNER: WATER WIRDLINGES DEPTSTART CARD) # 7134  (3) OWNER: WATER WIRDLINGES DEPTSTART CARD) # 7134  (4) OWNER: WATER WIRDLINGES DEPTSTART CARD) # 7134  (5) LOCATION OF WELL by legal description:			
Name State Highway DivisionSALEM, OREGON  Address 63055 North Highway 07			
Address 63055 North Highway 97	Township 8S Nor S. Range 15E	E or W	ww
City Bend State Oregon Zip 97701	Section 9 NW 14 NE	1/4	
(2) TYPE OF WORK:	Tax Lot 901 Lot Block		
New Well Deepen Recondition Abandon	Street Address of Well (or nearest address)		
(3) DRILL METHOD	<u>Cow Canyon Rest Area</u>		
Image: Row of the control of the c	(10) STATIC WATER LEVEL:		-
U Other (4) PROPOSED USE:	395 ft. below land surface.	Date6_	1-89
☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation	Artesian pressure lb. per square inch.	Date	
☐ Thermal ☐ Injection 🐰 Other Rest Area	(11) WATER BEARING ZONES:		
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found 48	35 <b>'</b>	
Special Construction approval Yes No Depth of Completed Well 540 ft.	From To Estin	nated Flow Rate	SWL
Yes No	485' 487'	5_CPM	395.
TIOY 71 -			
Diameter From To Material From To sacks or pounds			
10" 0 19' Bentonite 0 19' 8 sacks	(10) WELL LOC		l
-6# 519 <del>15</del> 540'	(12) WELL LOG: Ground elevation un	known	
	Material	From To	SWL
How was seal placed: Method	Top Soil & Boulders	0 4	
EXOther Poured Down	Hard Grey Basalt	4 55	
Backfill placed fromft. toft. Material	White Clay Conglomerate	55 105	
Gravel placed fromft. toft. Size of gravel	Broken Basalt Hard Brown Basalt	105   115 115   132	
(6) CASING/LINER:	Hard Grey Basalt	132 190	
Diameter From To Gauge Steel Plastic Welded Threaded	Mild Grey Basalt	190 208	
Casing: 6" +1 19' 250 X	Mild Brown Basalt	208 226	
	Mild Black Basalt	226 264	
	Hard Black Basalt	264 280	
Liner:	Lt. Brown Hard Clay	280 289	
Liner:	Mild Black Basalt	289 308	
Final location of shoe(s)	Hard Grey Basalt	308 323	
(7) PERFORATIONS/SCREENS:	Mild Black Basalt Mild Black Basalt	323 333 333 348	
Perforations Method	Hard Grey Basalt	348 418	
Screens Type Material	Mild Brown Basalt	418 425	
Slot Tele/pipe	Mild Black Basalt	425 449	
From To size Number Diameter size Casing Liner	Hard Grey Basalt	449 475	,,,
none	Mild Black Basalt	475 485	205
	White-Yellow, Hard Clay, W/B	485 540	395
	Date started 5-27-89 Completed	6-1-89	****
	(unbonded) Water Well Constructor Certificati	on.	·
(8) WELL TESTS: Minimum testing time is 1 hour Flowing	I certify that the work I performed on the co	nstruction, altera	ition, or
Pump Bailer Air Artesian	abandonment of this well is in compliance with 0 standards. Materials used and information reported	Dregon well cons	truction
Yield gal/min Drawdown Drill stem at Time	knowledge and belief.	above are true to	my best
5 535 1 hr.		WC Number _1;	
5 535 2 hr.	Signed D	ate <u>6–17–89</u>	9
(bonded) Water Well Constructor Certification:			
Temperature of water 59* Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. all			
work performed during this time is in compliance with Oregon well			
Did any strata contain water not suitable for intended use? $\Box$ Too little construction standards. This report is true to the best of my knowledge and			
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other		WC Number $\frac{6}{200}$	78
Departor strate:	Signed Discours Da	ate 6-17-89	1