NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORTE GEIVED

STATE OF OREGON MAY 201975 State Well No. 85-166-21

STATE ENGINEER, SALEM, OREGON 9731 ASC within 30 days from the date of well completion.

(Please type or print) STATE ENGINEE State Permit No. 003895 (Do not write above this line) ALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Robert Hastings	County COSCO Driller's well number
Address P.O. Box AUTELONE, ORE.	NE 14 NE 14 Section 2 T. 8 S R. 16 E W.M.
	Bearing and distance from section or subdivision corner 72 1/10 5+
(2) TYPE OF WORK (check):	+ 1140 South of NF Corner Sec. 21
New Well □ Deepening □ Reconditioning Abandon □	
If abandonment, describe material and procedure in Item 12.	CHAN THA MOTOR TENTINE CO. I. I. II
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotony M. Drivon D	Depth at which water was first found 35 ft.
Cable Jetted Domestic Industrial Municipal	Static level / ft. below land surface. Date 9/7/73
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(10) TUTTE T OC
10 " Diam from O ft. to 260 ft. Gage 109Ay E.	(12) WELL LOG: Diameter of well below casing
"Diam from ft. to ft. Gage	Depth drilled 315 ft. Depth of completed well 315 ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes \(\square\) No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used to seh Cut.	MATERIAL From To SWL
Size of perforations 6 in. by 1/2 in.	DUER BURDEST C 10
/20 perforations from b ft. to 20 ft.	
380 perforations from 220 ft. to 260 ft.	BOLD 4 CLAY - 10 50
perforations fromft. toft.	/
	BROWN ROCK BROKEN
(7) SCREENS: Well screen installed? Yes No	1 W ATER BEARING 50 140
Manufacturer's Name	<u> </u>
Type Model No.	BOLD & GREEN CLAY 140 220
Diam. Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	BADWH 1-1 4VEL 120 250
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	G-RAY ROCH HARD 250 315
Was a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
Harry Control of History Harry	
" " " " " " " " " " " " " " " " " " "	
Bailer test /00 gal./min. with O ft. drawdown after 2 hrs.	
Artesian flow g.p.m.	
perature of water & Depth artesian flow encountered ft.	Work started 4/7 19 75 Completed 4/9 1975
perature of water 8 Depth artesian now encountered	,//
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4/9 1995
Well seal-Material used Portland Comont	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bord below seal in.	[Signed] 7 77 /5 dieg Date 1/1/75, 19
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Contidiontions
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the pest of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name 11/ log 3 JOB DRIVIDY Co.
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address H. L. BOX 1/67 DEUJ, ORE.
Method of sealing strata off	resident VSD MCL
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	594 - 4/10 75
The UU	Contractor's License No, 1925