NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT CEIVED

	_	00111	1.1=	- YO A-
State	Well No.	8511	<i>e</i> =	

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON APR 1 6 1975

(Please type or printSTATE ENGINEER State Permit No. .... (Do not write above this line) EM, OREGON

	The state of the s	
(1) OWNER: 003911	(10) LOCATION OF WELL:	
Name LES Som OLL WOOD	County WASCO Driller's well num	iber
Address P.O. BOX ANTELOPE, ORE.	SE 4NE4 Section 29 T. 85 F	2. /6 E W.M.
	Bearing and distance from section or subdivision	corner
(2) TYPE OF WORK (check):	. 3	
New Well 💆 Deepening 🗌 Reconditioning 🔲 Abandon 🖂		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	II.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	140 ft.
Rotary M Driven D Domestic Industrial Municipal Cable	Static level \$0 ft. below land su	rface. Date 4// 7/75
Dug Bored I Irrigation Test Well NO Other	Artesian pressure lbs. per square	inch. Date
(5) CASING INSTALLED: Threaded Welded 17 12 "Diam from 1 ft. to 3 ft. Gage 250	(12) WELL LOG: Diameter of well be Depth drilled 300 ft. Depth of complet	
" Diam. from ft. to ft. Gage ft. Gage	Formation: Describe color, texture, grain size an and show thickness and nature of each stratum with at least one entry for each change of formatic	and aquifer penetrated,
PERFORATIONS: Perforated?  Yes X No.	position of Static Water Level and indicate princi	pal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	OVER BURDEN	0 10
perforations from ft. to ft.	BROWN CLAY	10 102
perforations from ft. to ft.		80
(7) SCREENS: Well screen installed?   Yes No	LIGHT BROWN CLAY	102 131
Manufacturer's Name	CRAVEL BROWN 4	
TypeModel No		131 220
Diam Slot size Set from ft. to ft.	WATER BEARING	
Diam. Slot size Set from ft. to ft.		434 345
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BROWN CLAY	2 20 2 45
Was a pump test made?   Yes No If yes, by whom?	GREEN CLAY	845 285
gal./min. with ft. drawdown after hrs.	BROWN Chay	285 300
" " " " " "	,	
Bailer test 9 hy; gal./min. with 0 ft. drawdown after 2 hrs.	- A Section of the se	
tesian flow g.p.m.		
mperature of water (7) Depth artesian flow encountered ft.	Work started 4/3/75 19 Completed	14/14/76 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1/4/75 19
Community of the second	Drilling Machine Operator's Certification:	
Well seal—Material used	This well was constructed under my	
Diameter of well bore to bottom of sealin.	Materials used and information reported abest knowledge and belief.	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 4/7/75 19
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	201
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	400
Brand name of bentonite	Water Well Contractor's Certification:	. <del>*</del>
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdic	tion and this report is
of water Ibs./100 gals.	true to the best of my knowledge and beli	ef.
Was a drive shoe used?  Yes No Plugs Size: location ft.	Name 1/1/Co43 Jos 02:1	ling Loo
Did any strata contain unusable water?   Yes No	Address Addres	BEUI ORE
Type of water? depth of strata	Address Co. Dox 1161	
Method of sealing strata off	[Signed] (Water Well Contra	ector)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No.5.14. Date A	
Gravel placed from ft. to ft.	Contractor's License Not. X. X Date X.X.	F