

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

RECEIVED

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WASCO

STATE OF OREGON FEB 18 1975
(Please type or print) STATE ENGINEER
SALEM, OREGON

State Well No. 85/16E-36dd
State Permit No. G 6855

003918 (Do not write above this line)

(1) OWNER:

Name Frank McNamee
Address Box 57 Antelope, Ore.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

(4) PROPOSED USE (check):

Rotary Driven
Cable Jetted
Dug Bored Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

8" Diam. from ±1 ft. to 19 ft. Gage 250
" Diam. from _____ ft. to _____ ft. Gage _____
" Diam. from _____ ft. to _____ ft. Gage _____

PERFORATIONS:

Perforated? Yes No.

Type of perforator used _____
Size of perforations in. by in.
_____ perforations from _____ ft. to _____ ft.
_____ perforations from _____ ft. to _____ ft.
_____ perforations from _____ ft. to _____ ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name _____
Type _____ Model No. _____
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? _____
Yield: _____ gal./min. with _____ ft. drawdown after _____ hrs.
Cased with Air Rotary - approx 200" gals per min Blown over top of casing.
Bailer test _____ gal./min. with _____ ft. drawdown after _____ hrs.
Artesian flow _____ g.p.m.

Temperature of water 48 Depth artesian flow encountered _____ ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 11 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 8 sacks
Number of sacks of bentonite used in well seal _____ sacks
Brand name of bentonite _____
Number of pounds of bentonite per 100 gallons _____
of water _____ lbs./100 gals.
Was a drive shoe used? Yes No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number _____
1/4 SE 1/4 Section 36 T. 8-S R. 16E W.M.
Bearing and distance from section or subdivision corner _____

(11) WATER LEVEL: Completed well.

Depth at which water was first found 190 1/30/75
Static level 35 ft. below land surface. Date ~~2/5/75~~
Artesian pressure _____ lbs. per square inch. Date _____

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 238 ft. Depth of completed well 238 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brn. Clay	0	30	
Brn. Rock - med.	30	218	
Brn. Rock - Hard	218	238	35

Work started 3/25/75 Completed 1/29/75
Date well drilling machine moved off of well 1/30/75

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Wm. M. Cunningham Date 2/5, 1975
(Drilling Machine Operator)

Drilling Machine Operator's License No. 522

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Cunningham Well Drilling
(Person, firm or corporation) (Type or print)

Address Box 104 Bend, Ore.

[Signed] Wm. M. Cunningham
(Water Well Contractor)

Contractor's License No. 474 Date 2/5, 1974

(USE ADDITIONAL SHEETS IF NECESSARY)