

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy of this report  
are to be filed with the

WATER RESOURCES DEPARTMENT,  
SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

WASCO  
50511

STATE OF OREGON  
(Please type or print)

RECEIVED

OCT - 1 1985

State Well No. 2W/12E-5bc  
State Permit No. ....

WATER RESOURCES DEPT.

(1) OWNER:

Name Albert E. Stevens  
Address 1625 State Road  
Mosier, Oregon 97040

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Driven   
Cable  Jetted   
Dug  Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

CASING INSTALLED:

Threaded  Welded

6" Diam. from 2 ft. to 31 ft. Gage 375  
" Diam. from ..... ft. to ..... ft. Gage .....  
" Diam. from ..... ft. to ..... ft. Gage .....

PERFORATIONS:

Perforated?  Yes  No.

Size of perforations in. by in.  
perforations from ..... ft. to ..... ft.  
perforations from ..... ft. to ..... ft.  
perforations from ..... ft. to ..... ft.

(7) SCREENS:

Well screen installed?  Yes  No

Manufacturer's Name .....  
Type ..... Model No. ....  
Diam. ..... Slot size ..... Set from ..... ft. to ..... ft.  
Diam. ..... Slot size ..... Set from ..... ft. to ..... ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made?  Yes  No If yes, by whom? owner  
Yield: 16 1/2 gal./min. with 80 ft. drawdown after 9 hrs.  
" " " " " " "  
" " " " " " "  
Baller test 33 gal./min. with 80 ft. drawdown after 1 hrs.  
Artesian flow ..... g.p.m.

(9) CONSTRUCTION:

Well seal—Material used cement w/ 4% bentonite  
Well sealed from land surface to 31 ft.  
Diameter of well bore to bottom of seal 12 in.  
Diameter of well bore below seal 6 in.  
Number of sacks of cement used in well seal 12 sacks  
How was cement grout placed? pressure grouted

Was a drive shoe used?  Yes  No Plugs ..... Size: location ..... ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? ..... depth of strata .....  
Method of sealing strata off .....  
Was well gravel packed?  Yes  No Size of gravel: .....  
Gravel placed from ..... ft. to ..... ft.

(10) LOCATION OF WELL:

County Wasco Driller's well number 70  
SW 1/4 SE 1/4 Section 5 T. 2 N R. 12 East W.M.

Bearing and distance from section or subdivision corner

TAX LOT 900

(11) WATER LEVEL: Completed well.

Depth at which water was first found 31 ft.  
Static level 22 ft. below land surface. Date 6/14/85  
Artesian pressure ..... lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 125 ft. Depth of completed well 125 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
dirt	0	12	
hardpan clay & gravel			
very hard yellowish brown	12	25	
loose gravel	25	29	
basalt, hard, black	29	97	22
claystone yellow, firm	97	99	22
basalt hard, black	99	112	22
claystone yellow firm	112	114	22
basalt hard black	114	125	22

Work started June 10 19 85 Completed July 2 19 85  
Date well drilling machine moved off of well July 3 1985

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Harry Douthit Date July 16, 1985  
(Drilling Machine Operator)  
Drilling Machine Operator's License No. 571

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Harry Douthit Well Drilling  
(Person, firm or corporation) (Type or print)  
Address 3343 Browns Creek Rd., The Dalles, Ore.  
[Signed] Harry Douthit  
(Water Well Contractor)  
Contractor's License No. 571 Date July 16, 1985