STATE OF OREGON

RECEIVED Wasc

WELL ID# L19611	_
-----------------	---

VELL I	D#	LISO	J T

WATER SUPPLY WELL REPORT (as required by ORS 537.765) (START CARD) # 101318 instructions for completing this report are on the last page of this form

(1) OW			Well Number:			County Mesos	F WELL by legal de	_atitude L	ongitude)
Name Address	Dane 8 5291 B	Paul Klindt aseline Dr.	2000	WAT	ER RESC SALEM.	UR ČESTDEPTAS OR ESON 9	N or S. Range <u>13E</u>	% SW	or W. of 1	WM.
			State OR	ZIP 97047		Tax Lot 2000	Lot Block Vell (or nearest address)	Subdiv	ision	
-	PE OF W						t Rd., Tygh Valley,			
New \	Vell 🗌	Deepening	ration (repair/recondit	on) Aban	donment	(10) STATIC WA				
•	ILL MET	HOD:		-		495 ft.	below land surface.		ate <u>9/2</u>	5/98
Rotar Other		Rotary Mud	Cable	Auger		Artesian pressure (11) WATER BEA		square mon.		-
4) PR	OPOSE	D USE:				(,	er was first found 330			
Dome		Community	☐ Industrial ☐ Livestock	x Irrigation ☐ Other	1	From	То	Estimated Flo	w Rate	ŞWL
Therr		Injection				290		15		237
		E CONSTRUCT				460	608	250		495
Special (Construction	on approval 🔲 Yes 🛭	No Depth of Cor	npleted Well _6	555 ft.					1
	es used { H OLE	_Yes∐x No Type	SEAL	Amount	unt	(40) WELL LOG:				
	From	To Materia	ı From 1	o sacks or	•	(12) WELL LOG :	Ground e	elevation		
14.75	. 0	340 Cement	018	16 Bag	8		Madanial	From	То	SWL
10"	340					Olave Hand Danie	Material n		15	SVVL
8"	611	655				Gravel & Clay R	rown	15	30	
						Sandstone Coa	rse Brown	30	52	
						Rock Soft Brok	en Black	52	61	-
		ed: Method LA	B X C D	E			ving		101 130	1
Othe		nft. to	ft. Material				Med. Hard Black	130	141	
Gravel (placed from	mft. to	ft. Size of grav	el		Rock Broken (F	oor Circulation)		160	
						Reselt Hard Gra	v	160	166	-
(6) CA	SING/L		Daniel Dies	tic Welded	Threaded	Sandstone Fine	Brown	166 190	190 196	
O:			Sauge Steel Plas				od Soft Lite Brown	1	240	
Casing.	10.75"	+1 489 .2		j 🖺		Clay Hard Gray			290	
						Gravel Med. Br	own Caving W/B	290	330	
							rse Brown W/B		335 382	+
Liner:					H	Claystone Brov	vn e Brown	335 382	405	
Einal la	cation of e	hoe(s) 490 ft		, LJ		Sandstone Cos	rse Brown	405	460	
						Gravel Med. W/	B	460	608	
(7) PE	RFORA	TIONS/SCREEN	15 :			Sandstone Har	d Brown	608	655	495
	Perforation		Mate						+	
	Screens	Type Slot	Tele/pip							
From	То	size Number	Diameter size	Casing	Liner					
				_						
				- 🗒		Date started 8/4/98		mpleted <u>9/25/9</u>	5	
	+					(unbonded) Wate	r Well Constructor Co	ertification:		
						I certify that the wo	rk I performed on the cons pliance with Oregon water	struction, aiteration, supply well constri	or aban	andards.
(8) W	FLL TE	STS: Minimum t	esting time is 1	hour		Materials used and in	nformation reported above	are true to my bes	knowle	dge and
Pun		Bailer	X Air	Flowin	-	belief.	•	WWC Nu		
Yield g	al/min	Drawdown	Drill stem at	Time		Signed				
250			655	1 hr.						
230						(bonded) Water V	Vell Constructor Cert	ification:		work
						I accept responsib	liity for the construction, a ell during the construction	niteration, or aband	VINMENT VIA AII	work
			Doub Adoles Flores			nerformed during thi	s time is in compliance wi	ith Oregon water su	pply wel	li
	erature of V	Vater <u>60</u> lysis done? Yes	Depth Artesian Flow for By whom	Juliu		construction standar	his sport is true to	the best of my know	ledge a	nd belief.
Was a	water ana oo etrata o	iysis done? 🔲 Tes ntain water not suitabl	le for intended use?	Too little				WWC Nu	mber;	790
Salf	ty 🔲 Mu	iddy 🗌 Odor 🔲	Colored Other_			Signed 4		Dete	10/21	98
						_ <u> </u>	stin Well Drilling			