RECEIVED

WASC 50896

STATE OF OREGON

WATER SUPPLY WELL REPORT

(as required by ORS WATER RESOURCES DEPT.

Instructions for completing the EMT OREGON ast page of this form. 45712 WELL I.D. # L__ START CARD # 136104

(1) OWNER: Well Number	(9) LOCATION OF WELL by legal description:	_
Name TIMOTHY DAHLE	County WASCO Latitude Longitude	
Address 5070 CHERRY HEIGHTS RD.	Township 1S N or S Range 12E E or W. WM.	_
City THE DALLES State OR Zip 97058		
(2) TYPE OF WORK	Tax Lot 600 Lot Block Subdivision	
X New Well Deepening Alteration (repair/recondition) Abandonment		- -
(3) DRILL METHOD:	DUFUR OR	A KD
	(10) STATIC WATER LEVEL:	=
Other	192 ft. below land surface. Data 1/30/00	
(4) PROPOSED USE:	Artesian pressure lb. per square inch. Date	-
	(11) WATER BEARING ZONES:	=
Domestic Community Industrial Irrigation Thermal Injection Livestock Other	(11) WATER BEARING ZONES:	
(5) BORE HOLE CONSTRUCTION:	F Double 4 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
• •	Depth at which water was first found 267	_
Special Construction approval Yes No Depth of Completed Well 525ft.		٦
Explosives used Yes No Type Amount	From To Estimated Flow Rate SWI 267 305 75-100 crom 192	⊣ 1
HOLE SEAL		
Diameter From To Material From To Sacks or pounds 15" 0 160 Cem/Bent 0 160 94SKS w/ge	192 436 504 150+ gpm 192	4
		4
12" 160 200 Cem/Bent 160 200 10SKS w/ge		-
10" 200 525		╛
	(12) WELL LOG:	
How was seal placed: Method A B B C D E	Ground Elevation	_
Other		_
Backfill placed from ft. to ft. Material	Material From To SWL	4
Gravel placed from ft. to ft. Size of gravel	Brown clay, occ. rocks 0 6	4
(6) CASING/LINER:	Brown basalt (boulder) very 6 11	4
Diameter From To Gauge Steel Plastic Welded Threaded		_
Casing: 10" +2 200.250 X	Brown sandstone w/basalt 11 50	4
	boulders	_
	Gray-brown sanstone w/volcanic50 155	_
	Brown basalt, broken 155 175	_
Liner:	Black&gray-black basalt, hard 175 210	
	Brown basalt, occ. brown clay- 210 225	_
Final location of shoe(s)	stone	_
(7) PERFORATIONS/SCREENS:	Brown&gray-brown basalt, frac 225 240	_
Perforations Method	Gray-brn, gray-blk, basalt, hard 240 267	
Screens Type Material	Brown basalt, brkn, occ. claystn. 267 305 192	
Slot Tele/pipe From To size Number Diameter size Casing Liner	Drown corner ham be sell from 1 205 245	
	Gray-brn, gray-blk, basalt, frc, 315 436	
	Brown&gray-brn basalt,brkn, 436 504 192	
	occ.gray-black strks.occ.ash/claystone	
	Blue-gray claystone/siltstone 504-525	_
	NEED TO TEST PUMP WELL, SET PUMP @ 450'+/-	
(8) WELL TESTS: Minimum testing time is 1 hour	Date started 11/09/00 Completed 11/30/00	_
Flowing	(unbonded) Water Well Constructor Certification:	_
Pump Bailer XAir Artesian	I certify that the work I performed on the construction, alteration, or abandonmer	t
Yield gal/min Drawdown Drill stem at Time	of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge	
250+ 500 1 hr.	and belief.	
165–200 400 "	WWC Number	
130 300 "	Signed Date	•
Temperature of water 59°F Depth Artesian Flow Found	(bonded) Water Well Constructor Certification:	Ξ
Was a water analysis done? X Yes By whom AMT	I accept responsibility for the construction, alteration, or abandonment work	
Did any strata contain water not suitable for intended use? Too little	performed on this well during the construction dates reported above. All work	
Salty Muddy Odor Colored Other	performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.	
Depth of strata:	WWC Number 573	
	Signed Date 11/30/00	ī
		<u> </u>
ORIGINAL – WATER RESOURCES DEPARTMENT FIRST COPY – CO	CONSTRUCTOR SECOND COPY – CUSTOMER	