STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) WASC 52158

WELL ST ORIG

		Page 1 01 1
L I.D. LABEL# L	114530	
TART CARD#	1023542	
GINAL LOG#		

(as required by ORS 537.765 & OAR 690-205-0210)	7/6/2014 ORIGINAL LOG #
(1) LAND OWNER Owner Well I.D.	
First Name LARRY Last Name CLARK	(9) LOCATION OF WELL (legal description)
Company CAMP BALDWIN	County wasco Twp 2.00 S N/S Range 11.00 E E/W V
Address 76201 DUFUR VALLEY RD	- Sec 9 SE 1/4 of the SW 1/4 Tax Lot N/A
City DUFUR State OR Zip 97021	
(2) TYPE OF WORK New Well Deepening Conversi	on Lat ° ' " or 45.40447222 DMS or D
Alteration (complete 2a & 10) Abandonment(comp	Long Or -121.43211111 DMS or D
Dia + From To Gauge Stl Plstc Wld Thrd	 Street address of well Nearest address
Casing:	76201 DUFUR VALLEY RD
Material From To Amt sacks/lbs	
Seal:	(10) STATIC WATER LEVEL
X Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWL(psi) + SWL(ft)
Reverse Rotary Other	Existing Well / Pre-Alteration
	Completed Well 7/3/2014 194
(4) PROPOSED USE Domestic Irrigation Community	Flowing Artesian? Dry Hole?
Industrial/ Commericial Livestock Dewatering	WATER BEARING ZONES Depth water was first found 230.00
Thermal Injection Other	SWL Date From To Est Flow SWL(psi) + SWL(ft)
(5) BORE HOLE CONSTRUCTION Special Standard (Atta	ch copy) 6/27/2014 230 252 50 194
Depth of Completed Well 276.00 ft.	
BORE HOLE SEAL	sacks/
Dia From To Material From To Amt	lbs S
12 0 217 Bentonite Chips 0 3 3 8 217 276 Cement 3 217 65	S
0 217 270 Centent 3 217 03	
	(11) WELL LOG Ground Elevation 3782.00
How was seal placed: Method A B XC D	
X Other POURED DRY	CLAY BROWN 0 1
Backfill placed from ft. to ft. Material	BOULDERS CLAY
Filter pack from ft. to ft. Material Size	BASALT CLAY BROWN 32 38
Explosives used: Yes Type Amount Amount	BASALT GRAY 38 62
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	SANDSTONE BROWN CLAY 62 78
Proposed Amount Actual Amount	BASALT LIGHT GRAY HARD 78 128
(6) CASING/LINER	CLAY GRAY 128 134
Casing Liner Dia + From To Gauge Stl Plstc Wle	1 Thrd BASALT DARK GRAY FRACTURED 134 142 158 142 158
● 8 X 2 217 .250 ● X	CLAY WITH BASALT 158 170
	SANDSTONE BROWN 170 192
	SANDSTONE CLAY BROWN 192 212
	SANDSTONE BASALT 212 218
Shoe Inside Outside Other Location of shoe(s)	CONGLOMERATE BROWN 218 252 CLAY BROWN RED 252 276
Temp casing Yes Dia From To	CLAT BROWN RED 232 270
7) PERFORATIONS/SCREENS Perforations Method	
Screens Type Material	Date Started6/27/2014 Complete 7/3/2014
Perf/ Casing/ Screen Scrn/slot Slot # of	Tele/
Screen Liner Dia From To width length slots p	pe size (unbonded) Water Well Constructor Certification I certify that the work I performed on the construction, deepening, alteration,
	abandonment of this well is in compliance with Oregon water supply w
	construction standards. Materials used and information reported above are true
	the best of my knowledge and belief.
	License Number 758 Date 7/6/2014
8) WELL TESTS: Minimum testing time is 1 hour	Signed TYOMAG P PROVIDE TO THE
Pump Bailer Air Flowing Artes	ian Signed THOMAS R PECK (E-filed)
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification
50 240 4	I accept responsibility for the construction, deepening, alteration, or abandonr
	work performed on this well during the construction dates reported above. All v
	performed during this time is in compliance with Oregon water supply construction standards. This report is true to the best of my knowledge and belie
Temperature 55 °F Lab analysis Yes By	
Water quality concerns? Yes (describe below) TDS amount From To Description Amount U	License Number 1720 Date 7/6/2014
2 Description	Signed JACK ABBAS (E-filed)
	Contact Info (optional)
ODICINAL WATER DESCRI	