STATE OF OREGON WATER SUPPLY WELL REPORT WASC 52567

WELL I.D. LABEL# L $_{2043}$ **START CARD** # 1037699

(as required by ORS 537.765 & OAR 690-205-0210)	3/25/2	ORIGINAL LOG #	
(1) LAND OWNER Owner Well I.D.			
First Name Last Name		(9) LOCATION OF WELL (legal description)	
Company SADDLE VIEW ORCHARDS		County WASCO Twp 2.00 N N/S Range 12.0	00 E E/W WM
Address 1120 STATE RD.		Sec <u>6 SW 1/4 of the NE 1/4 Tax Lot</u>	
City MOSIER State OR Zip 97040 (2) TYPE OF WORK New Well Deepening Conversion	= 1	Tax Map Number Lot	
Alteration (complete 2a & 10) Abandonment(complete	on I	Tax Map Number Lot Lat ' ' ' or Long ' or	DMS or DD
(2a) PRE-ALTERATION		Long or	DMS or DD
Dia + From To Gauge Stl Plstc Wld Thrd		Street address of wellNearest address	
Casing:		1120 STATE RD., MOSIER, OR 97040	
Material From To Amt sacks/lbs Seal:	<u> </u>		
(3) DRILL METHOD	<u> </u>	(10) STATIC WATER LEVEL	
Rotary Air Rotary Mud Cable Auger Cable Mud		Date SWL(psi)	+ SWL(ft)
Reverse Rotary Other		Existing Well / Pre-Alteration Completed Well	
(4) PROPOSED USE Domestic Irrigation Community		Flowing Artesian? Dry Hole?	
Industrial/ Commercial Livestock Dewatering	,		
Thermal Injection Other	ľ	WATER BEARING ZONES Depth water was first four SWL Date From To Est Flow SWL(psi	
		SWL Date From To Est Flow SWL(psi) + SWL(II)
(5) BORE HOLE CONSTRUCTION Special Standard (Attac	ch copy)		
Depth of Completed Well ft. BORE HOLE SEAL	sacks/		
Dia From To Material From To Amt	lbs		-
Calculated			
Calculated	+ [7	(11) WELL LOG Ground Elevation	
How was seal placed: Method A B C D E	-	Material From	То
Other			
Backfill placed from ft. to ft. Material			
Filter pack from ft. to ft. Material Size	╟		
Explosives used: Yes Type Amount	lt		
(5a) ABANDONMENT USING UNHYDRATED BENTONITE			
Proposed Amount Actual Amount			
(6) CASING/LINER	<u> </u>		
Casing Liner Dia + From To Gauge Stl Plstc Wld	Thrd		
	$H \parallel$		
	H		
	\sqcap		
Shoe Inside Outside Other Location of shoe(s)	[
Temp casing Yes Dia From + To To			
(7) PERFORATIONS/SCREENS	— ⊩		
Perforations Method		D. G. Jananasa G. J. Jananasa	10
Screens Type Material Perf/ Casing/ Screen Scrn/slot Slot # of T	Tele/	Date Started 2/20/2018 Completed 3/20/20	18
· · · · · · · · · · · · · · · · · · ·	DC BIZE	(unbonded) Water Well Constructor Certification	
		I certify that the work I performed on the construction, deep abandonment of this well is in compliance with Oregon	
		construction standards. Materials used and information report	
		the best of my knowledge and belief.	
		License Number Date	
(8) WELL TESTS: Minimum testing time is 1 hour		Signed	
Pump Bailer Air Flowing Artesia	ian _		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)		(bonded) Water Well Constructor Certification	
	_ [1	I accept responsibility for the construction, deepening, alterat	ion, or abandonment
		work performed on this well during the construction dates report performed during this time is in compliance with Oregon	
Temperature °F Lab analysis Yes By		construction standards. This report is true to the best of my known	
		License Number 1879 Date 3/25/2018	
Water quality concerns? Yes (describe below) TDS amount 110 p From To Description Amount United States of the Property of the	nits		
	<u> </u>	Contact Info (optional) Mike	
ODICINAL WATER RECOIL	IDCEC DE	DARTMENT	

WASC 52567

WELL I.D. LABEL# L 2043

START CARD # 1037699

ORIGINAL LOG #

continuation page	3/25/2018		ORIGINAL L	OG #	<u> </u>	
2a) PRE-ALTERATION	Water	Quality Cor	ncerns			
Dia + From To Gauge Stl Plstc Wld Thrd	From	То	Descri	ption	Amou	ınt Units
Material From To Amt sacks/lbs						
5) DODE HOLE CONCEDUCTION	$\overline{(10) \text{ S}}$	TATIC WA	TER LEVEL			
5) BORE HOLE CONSTRUCTION	SWL	Date Fron	n To	Est Flow	SWL(psi)	+ swl
BORE HOLE SEAL Dia From To Material From To Amt	sacks/					
Macha Hom 10 Am	108			+		
Calculated						
				++		
Calculated						
Calculated						
Calculated						
FILTER PACK						
From To Material Size	(11) W	ELL LOG				
		Mate	erial		From	То
6) CASING/LINER						
Casing Liner Dia + From To Gauge Stl Plstc Wld T	Thrd					
	\neg \vdash					
8 9 H						
	Ы					
7) PERFORATIONS/SCREENS						
0	Tele/ ipe size					
Profit 10 Width length Slots b	ipe size					
					_	
	Comn	nents/Rema	rks			
(O) YVIDY I (DECIDE AND A COLOR OF A COLOR O		ed 90 feet of 8				
(8) WELL TESTS: Minimum testing time is 1 hour	D-11- 4 4		et around 10 inch	casing.		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr		53 feet of 10 in oned with 288 b	ch casing. pags of bentonite s	creened.		
		200 0	₀ 5 01 00mome 5			
] []					