NOTICE TO WATER WELL CONTRACTOR WAS WATER WELL REPORT. WE filed with the

STATE OF OREGONIAN 29 1973

State Well No.

STATE ENGINEER, SALEM, OREGON 9730 10290 within 30 days from the date of well completion.

(Please type of print) TE ENGINEER
(Do not write above SALEM OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name Lyle Cobb Crushed Rock	County Washington Driller's well number		
Address 8275 S. W. Murray Blvd.	14 14 Section 26 T. 1 S R. 2 W. W.M.		
Beaverton, Oregon 97005	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐		-	······································
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL. Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well. Depth at which water was first found 401 ft.		
Potenty M Driven D			
Cable	Static level 293 ft. below land s	urface. Date 1/	22/73
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square	e inch. Date	
CASING INSTALLED: "Diam. from X ft. to X ft. Gage X "Diam. from X ft. to X ft. Gage X "Diam. from X ft. to X ft. Gage X "Diam. from X ft. to X ft. Gage X PERFORATIONS: Perforated? Yes X No.	(12) WELL LOG: Diameter of well below casing 4-7/8 Depth drilled 142 ft. Depth of completed well 472 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used X	MATERIAL	From To	swl
Size of perforations X in. by in.	Previously drilled	0 330	
perforations from ft. to ft.	Brown & gray rock	330 365	
perforations from X ft. to ft.	Hard gray rock	365 401	
perforations from ft. to ft.	Gray & brown rock	401 409	6 gpm
	Hard brown & gray rock	409 422	
(7) SCREENS: Well screen installed? ☐ Yes 🖾 No	Brown rock	422 431	
Manufacturer's Name	Brown & gray rock	431 443	
Type Model No.	Hard gray rock	443 447	0
Diam Slot size Set from ft. to ft.	Broken & perforated rock	447 466	9 gpm
Diam. Slot size Set from ft. to ft.	Brown rock	466 472	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Note: Diameter of well 330-4	72 h-7/8"	
Was a pump test made? ☐ Yes 🖫 No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
airlift of of			 ·
Bailer test 15 gal./min. with 167 ft. drawdown after 2 hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 1/8/73 19 Complete	ed 1/22/73	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1/23/73	19
Well seal—Material used X	Drilling Machine Operator's Certification: This well was constructed under my Materials used, and information reported best knowledge and belief. [Signet Luc Luc Luc Machine Operator) Drilling Machine Operator's License No.	above are true Zate 1/24/7	to my
Number of sacks of bentonite used in well seal sacks	The state of the s		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 ^X gallons	This well was drilled under my jurisdiction and this report is		
of water lbs./100 gals. Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.		
was a drive snoe used? \square Yes \square No Plugs	Name A. M. Jannsen Drilling Co. (Person, firm or corporation) (Type or print)		
Y	Address 21075 S. W. Tualatin Va	lley Hwy, A	Ĭoha, Or
X	EATONO()	· · · · · · · · · · · · · · · · · · ·	
Method of sealing strata off	[Signed] (Water Well Contr	une	**********
Was well gravel packed? Yes No Size of gravel:		² 24/73	10
Gravel placed from ft. to ft.	Contractor's License No(2 Date		, 19