

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON, within 30 days from the date of well completion.

RECEIVED JUN 13 1969 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON (Please type or print) (Do not write above this line)

010693

State Well No. 1/3W-14

State Permit No.

(1) OWNER:

Name W. A. Gilbert Address Rte 2 Box 240 Cornelius, Ore

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

8" Diam. from 0 ft. to 92 ft. Gage 1/2 wall 7" Diam. from 87 ft. to 135 ft. Gage 1/2 wall

PERFORATIONS:

Perforated? [X] Yes [] No [] Type of perforator used torch Size of perforations 1/8 in. by 6 in. 50 perforations from 87 ft. to 135 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 30 ft. below land surface Date 5-27-69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Bailer test 100 gal./min. with 85 ft. drawdown after 1 hrs. Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used Bentonite Depth of seal 90 feet Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [] Yes [X] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Washington Driller's well number 1/4 1/4 Section 14 T. 1-S R. 3-W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 7 inch Depth drilled 135 ft. Depth of completed well 135 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil, Yellow clay, Yellow sandy clay, Blue fine sandy clay, Grey clay, course black sand & pea gravel.

Work started 5-26-69 19 Completed 5-27-69 19 Date well drilling machine moved off of well 5-27-69 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ralph Turner Date 5-31, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 254

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Ralph Turner Drilling Co. (Person, firm or corporation) (Type or print)

Address Rte 1 Box 141 Hillsboro, Oregon

[Signed] Ralph Turner (Water Well Contractor)

Contractor's License No. 247 Date 5-31-1969