WATER WELL REPORT STATE OF OREGON

Should be not all of WASH 0107415/3W-17dd
Should be not all of EC State Well No. 15/3W-17dd

Should be not all of EC State Well No. 15/3W-17dd

~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	NATER RESOURCES DEPT! Recondition
(1) OWNER:	(10) Loca Proposition Well:
Name Donald B. Anderson	TT =1 to subsect
Address Route 4, Box 137L	
City Cornelius, Oregon State 97113	7
	Tax Lot # Lot Blk Subdivision  Address at well location:
(2) TYPE OF WORK (check):	Address at well location.
New Well □ Deepening □ * Reconditioning ■ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
	Static level 20 ft. below land surface. Date $\frac{5}{28}$
Rotary Air 🚺 Driven 🗆 Domestic 🖸 Industrial 🗎 Municipal 🗆  Rotary Mud 🗆 Dug 🖂 Irrigation 🛣 Test Well 🗎 Other 🖂	Artesian pressure lbs. per square inch. Date
Bored □ Thermal: Withdrawal □ Reinjection □	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel N Plastic	Depth drilled — ft. Depth of completed well ft.
(5) CASING INSTALLED: Steel X Plastic  Threaded  Welded X	Formation: Describe color, texture, grain size and structure of materials; and show
6" Diam. from10 ft. to340 ft. Gauge188	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
"Diam. from ft. to ft. Gauge	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWI
-	Hole blocked @ 335', and
	cleaned out to bottom.
(6) PERFORATIONS: Perforated? X Yes \( \square\) No	Liner installed - did not fall
Type of perforator used Torch	to bottom.
Size of perforations 1/4 in. by 12 ¹¹ in.	00 000000
60 perforations from 310 ft. to 340 ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ☐ Yes XNo	
Manufacturer's Name	
Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
Drawdown is amount water level is leveled	
(8) WELL TESTS:  below static level	
a pump test made?    Yes  No If yes, by whom?	
held: 180 gal./min. with 180 ft. drawdown after 2 hrs.	
n " "	
Air test gal./min. with drill stem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
esian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	5/07/09 F/00/00
(a) CONCERNICENON	Work started 5/27/82 19 Completed 5/28/82 19
(9) CONSTRUCTION: Special standards: Yes □ No □ Well seal—Material used X	Date well drilling machine moved off of well $5/28/82$ 19
	Drilling Machine Operator's Certification:
Well sealed from land surface to X	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal in.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 6/4/., 19.82
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 751
How was cement grout placed?	
X	Water Well Contractor's Certification:
The state of the s	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was pump installed?	Name A. M. JANNSEN WELL DRILLING CO. INC.
Was a drive shoe used? Yes No Plugs Size: location ft.	(Type or print) Address 21075 SW Tualatin Valley Hwy. Aloha, Or
Did any strata contain unusable water?	Address 21075 SW Tualatin Valley Hwy. Aloha, Or
Type of Water? depth of Arata  Method of sealing strata off	[Signed] Short Ill Jehnen
	(Water Well Contractor)
Was well gravel packed?     □ Yes     □ No     X Size of gravel:       Gravel placed from     ft. to     X	Contractor's License No79 Date June 4, 1982 , 19
	1