ate with the re Engineer, MAY	ATTERWELL DRILL 8 1957 STATE OF OR	
LEM. OREGON	ENGINEER	
(1) OWNER: SIALE Name Jim Harder CALEN	, OREGON WAS	(10) WELL TESTS: Was a pump test made? X Yes 🗆 No If yes, by whom? Well drille:
· · · · · · · · · · · · · · · · · · ·		Yield: gal./min. with ft. draw down after hrs. "120 25 " 4 "
Portland, Oregon	8 m	<u> </u>
(2) LOCATION OF WELL:		Artesian flow
County Washington Owner's number	, if any	Shut-in pressure lbs. per square inch.
R. F. D. or Street No. Rt. 1 Bx 629 - T		Bailer test g.p.m. with ft. drawdown
Bearing and distance from section or subdivision corner N - 27° -55' W, 796.4 ft. from SE corner Sec. 10, T2S, R1W, W.M.		Temperature of water Was a chemical analysis made? 🗌 Yes 🗶 No
		Was electric log made of well? 🗌 Yes 🕱No
		(11) WELL LOG:
		Diameter of well, inches.
(3) TYPE OF WORK (check): New well □ Deepening ★ Reconditioning □ Abandon □ abandonment, describe material and procedure in Item 11.		Total depth 353 ft. Depth of completed well 353 ft.
		Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each
		show inconess of aquifers and the kind and mature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check):	(5) EQUIPMENT:	$\frac{\text{ft. to} \qquad \text{ft.} \qquad =}{0  \text{"] 30  \text{" previously dvilled}}}$
Somestic X Industrial I Municipal	Cable 🕅	0 " 130 " previously drilled 130 " 157 " clay and rock
Irrigation 🛃 Test Well 🗌 Other	Dug Well	157 " 211 " brown clay
) CASING INSTALLED:	If gravel packed	211 " 254 " clay and rock
Threaded 😥 Welded 🗆	II glavel packeu	254 " 261 " cemented gravel
Gage or	Diameter from to	261 " 279 " clay and rock
FROM ft. to ft. Diam. Wall	of Bore ft. ft.	279 " 310 " cemented gravel
<u>"31 " " " "</u> "0 " 310 " "6" •280"		310 " 353 " gray basalt rock
<u> </u>		" " water bearing 351 to 353
<del>3</del> 5 31 23 29 33		
· · · · · · · · · · · · · · · · · · ·	>> 22	
Type and size of shoe or well ring 6" Stee!	Size of gravel:	1) I)
Describe joint Welded		
(7) PERFORATIONS:		1) 1)
Type of perforator used		23 29 
	length, by in.	17 I)
FROM ft. to ft. perf	per foot No. of rows	n n
21 11 12 23	33 33 33 33 33	
21 22 22 23	33 33 33 33 33	<u> </u>
, 19 13 39 32 32	39 22 39 59 59	<u> </u>
SCREENS:		
Give Manufacturer's Name, Model No.	and Size	)) )) 
	AP	n n
(d) CONSTRUCTION:		n n n n
Was a surface sanitary seal provided?		
Were any strata sealed against pollution? $\Box$ Ye If yes, note depth of strata	es 📋 ino	Ground elevation at well site feet above mean sea level. Work started 2-28-58 19 , Completed 4-5-57 19
FROM ft. to	ft.	
,, ,,	»»	Well Driller's Statement: This well was drilled under my jurisdiction and this report is
METHOD OF SEALING		true to the best of my knowledge and belief.
(9) WATER LEVELS:		NAME A.M. JANNEEN DRILLING COMPANY
Depth at which water was first found 351. ft.		(Person, firm, or corporation) (Typed or printed)
Standing level before perforating 15 ft.		Address "L 21075 S.W. Tualatin Valley Highway
Standing level after perforating	15 ft.	Driller's well number,
Log Accepted by:		[Signed] Swad Ul Janulla
[Signed], 19		(Wal Driller)
[Signed] Date	d	License No. 97 Dated 4-25-57 19