File Original and First Copy with the

SALEM, OREGON	STATE O	F OREGON State Permit No		
(1) OWNER:	STATE E			
Name T. C. Wasson	SALFM	lowered below static le	evel	
Address 6735 S. W. Pacific Hwy		Yield: gal./min. with ft. drawdov	m? ~	4
Tigard, Oregon		" " " " " "	vn arter	hrs
(2) I OCATION OF WELL		19 99		
(2) LOCATION OF WELL: <u>County Washington</u> Owner's num		Bailer test 35 gal./min. with 160 ft. drawdown after ), hrs.		
STILL COURT		Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision		Temperature of water 54 Was a chemical analysis m	ade? 🗆 Y	es 1KO No
Bearing and distance from section or subdivision	on corner			
		(12) WELL LOG: - Diameter of well		inches.
		Depth drilled 695 ft. Depth of completed w		ft.
	, , , , , , , , , , , , , , , , , , , ,	Formation: Describe by color, character, size of materi show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each of	al and stru the materi	cture, and al in each
		stratum penetrated, with at least one entry for each c	hange of j	formation.
		MATERIAL	FROM	TO
(3) TYPE OF WORK (check):		Brown silty clay	0	18
	litioning	Fine sand, brown	18	36
pandonment, describe material and procedu	re in Item 11.	Fine grey sand	36	58
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	Grey clay, gritty	58	_78
Domestic ☐ Industrial ☐ Municipal ☐	Rotary   Driven	Blue fine sand, trace of gravel	78	_79
Irrigation  Test Well  Other	Cable 🔼 Jetted 🗌	Brown grey and blue clay	79	_370_
Store and trailer court	Dug 🗌 Bored 🗎	Grey clay and course broken rock	370	385
(6) CASING INSTALLED: Three	raded [] Welded [X]	Grey conglomerate	385	500
6" Diam. from 0 ft. t526	-9" ft. Gage •250	Yellow conglomerate	500	_524_
		Soft grey rock with clay seams	524	<u> 553</u>
		Grey basalt rock	553	<u>680</u>
(E) DEDUCE A PROSEC		Soft black rock (water bearing) Hard grey rock	680	694
• /	forated? 🗌 Yes 🕱 No	naru grey rock	694	695
Type of perforator used		-		<del></del>
SIZE of perforations in. by	in.			
perforations from		the state of the s		
perforations from				
perforations from	· ·			
perforations from perforations				
periorations from	1t. W It.			
(8) SCREENS: Well screen ins	stalled 🗌 Yes 🏋 No			
ufacturer's Name				
Гуре М	odel No			
n Slot size Set from	ft. to ft.			
Diam Slot size Set from	ft. to ft.	Work started 6/11/62 19 . Completed 8	/13/62	19
CONSTRUCTION:		(19) DITAID.		
Was well gravel packed? ☐ Yes M No Size	of gravel:	(13) PUMP:	•	
Gravel placed fromft. toft.		Manufacturer's Name Jacuzzi		
Was a surface seal provided? XYes \( \Bar{\text{No}}\) No To what depth?21		Type: Submersible	H.P2	***************************************
Material used in seal—Bentonite and p	•	Well Driller's Statement:		
Did any strata contain unusable water? 🗵 Yes	v	This well was drilled under my jurisdiction a	and this a	enort is
Type of water Wood and bad tester to	trata 781 to 791	true to the best of my knowledge and belief.	AIIG VIIIS I	cport is
Method of sealing strata off 6 inch casi	ng	NIABER Stainman Proc		•
(10) WAMED TEXTERS.		NAME Steinman Bros. (Person, firm, or corporation) (T.	ype or print	:)
(10) WATER LEVELS:		Address 5112 S.E. McLoughlin, Milwaukie, Ore.		
Static level ft. below land s		+	•	
Artesian pressure ] 1b. lbs. per square inch Date 8/13/62		Driller's well number 34-62		
og Accepted by:		[Signed] Standard Systems (Well Driller)		-
igned]Date	í í í	· ·	?	
(Owner)	19	License No	<u>}</u>	, 19