4 NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

ATER WELL REPORT

State Well No.

of this report are the filed with the JUNE 4 1389 STATE OF OREGON

STATE ENGINEER, SALEM OREGON 97310 (Please type or print) within 30 days from the dated in the filed of well completions at the OFFICON

State Permit No. .

(1) OWNER: Porter Walton Co. Inc. Nursery Pat.	(11) LOCATION OF WELL:			=
Name Yoshio & Sachiko Hasuike	County Washington Driller's well nur	nber		
Address15685 S.W.150th.Ave.Tigard.Ore.97223	14 14 Section 16 T. 28		Ī	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	corner		
	•		-	
New Well 🛣 Deepening 🗆 Reconditioning 🗀 Abandon 🗀				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USÉ (check):	(12) WELL LOG: Diameter of well b	elow casin	<u>, 1</u>	2 H
Rotary Driven Domestic Industrial Municipal	Depth drilled 392 ft. Depth of comple	ted well	392	ft.
Dug 🗌 Bored 🗌 Irrigation 📆 Test Well 🗎 Other 📋	Formation: Describe color, texture, grain size a			otorials
CASING INSTALLED: Threaded Welded	and show thickness and nature of each strature			
CASING INSTALLED: Threaded Welded 250	with at least one entry for each change of forms			
	in position of Static Water Level as drilling pro-	eeas. No	te ariiin	
" Diam. from ft. to ft. Gage	MATERIAL	From	То	SWL
	Top soil	0	3	
PERFORATIONS: Perforated? Yes No.	Clay, yellow	3	7	
Type of perforator used	Rock, broken	7	8	
	Clay w/embeded rock	8	_40	
Size of perforations in. by in.	Sand, yellow	40	<u> 1</u> i2	27
perforations from ft. to ft.	Clay, yellow sandy	12	48	
perforations from ft. to ft.	Clay w/embeded rock	<u> 4</u> 8	50	
perforations from ft. to ft.	Rock, brown solid	_50_	118	
perforations from ft. to ft.	Clay, brown	118	126	
perforations from ft. to ft.	Rock, red lava soft,			
(7) SCREENS: Well screen installed? Yes No	water bearing	126	159	
Manufacturer's Name	Rock, black	159	197	
Type	Clay, yellow	197	198	
Diam. Slot size Set from ft. to ft.	Rock, black	198	358	
Diam. Slot size Set from ft. to ft.	Rock, gray, mdm. hard	358	370	
	Rock, brown, soft, w. brng.	370	389	60
(8) WATER LEVEL: Completed well.	Rock, black, hard	389	392	
Static level 60 ft. below land surface Date 6/18/69				
sian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is			•	
Was a pump test made? Yes No If yes, by whom? Bottner				
	Work started April 1 1969 Complete	d June	. 12	1969
Yield: 260 gal./min. with 50 ft. drawdown after 7 hrs.		June 2		1969
H-14 " 19 " E "	 .	/ VALUE E		
<u>"" " " " " " " " " " " " " " " " " " "</u>	Drilling Machine Operator's Certification:			36-4- ··
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my di rials used and information reported abov	rect supe e are tr	rvision. ue to n	ny best
Artesian flow g.p.m. Date	knowledge and belief.	_		
Temperature of water 51. Was a chemical analysis made? ☐ Yes 및 No	[Signed] Koring Machine Operator) Date 6 20, 19.6			
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	246-4:	31	
Well seal—Material used Cement & sand				
Depth of seal ft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is			
Were any loose strata cemented off? 🗌 Yes 🛣 No Depth	true to the best of my knowledge and belief. NAME HAAKON BOTTNER DRILLING COMPANY			
Was a drive shoe used? Yes No	(Person, firm or corporation)	(Type	or print)	
Did any strata contain unusable water? Y Yes No Type of water? Sandy depth of strata 110 to 112 to	Address 3424 S.E. 174 th. AV	I.PORT	CLAND	ORE.
Type of water? Sandy depth of strata 10 to 12! Method of sealing strata off cased	Hanker 18	0//	210	
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contract	tor)	e. Lestered.	Comment.
Gravel placed from the to the state of the s	Contractor's License No. 109 Date	1201		19.6.2