NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be

WASIWATER WELL REPORRECEIVED

STATE ENGINEER, SALEM, OREGON 90012055 within 30 days from the

STATE OF OREGON

DE63 1973tate Well No. 25 1W-27

of well completion.

(Do not write above this line) STATE ENGINESTRE Permit No. SALEM, OREGON

1		
(1) OWNER:	(10) LOCATION OF WELL:	1/70
Name DONALD M DRAKE CO.	County WAShing to Abriller's well nu	mber 4/0
Address 11/25 TUAL ITIN SHEAWOOD HIWA	YSE 1/4 SW1/4 Section 27 T. 28 R. /W W.M.	
TYJO NW FLANDERS PTLD. 97209	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	To HOU	
New Well Deepening Reconditioning Abandon	110 2012 100	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 360 ft.	
Rotary Driven Domestic Industrial Municipal D	Static level //O ft. below land surface. Date //8-2/	
Cable Jetted	Artesian pressure lbs. per square inch. Date	
·	Tit toblati probato	
(8) CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well b	elow casing
8 "Diam. from 71 ft. to 334 ft. Gage 1250	Depth drilled 400 ft. Depth of completed well 400 ft.	
	Formation: Describe color, texture, grain size a	nd structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in	
6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ	
	MATERIAL	From To SWL
Type of perforator used		0 20
Size of perforations in. by in.	SAND A BROWN SANDY	20 30
perforations from ft. to ft.	CLAY BROWN	3050
perforations from	CHAY BROWN SANDY	50 120
perforations from ft. to ft.	CLAY BROWN	120 130
(7) SCREENS: Well screen installed? ☐ Yes 🗘 No	CLAY VELLOW	130 150
Manufacturer's Name	CLAY BROWN	156 170
Type Model No.	SILT BROWN	170 334
Diam Slot size Set from ft. to ft.	BASALT	334 360
Diam Slot size Set from ft. to ft.	BASALT DECOMPOSED	360 450/10
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
lowered below stante level	Y 120 100 100 100 100 100 100 100 100 100	
Was a pump test made? Yes No If yes, by whom? Duller		
rield: 60 gal./min. with 290 ft. drawdown after 2 hrs.	The state of the s	
n n n		
<u>n</u> <u>n</u> <u>n</u>	The second secon	
Bailer test gal./min. with ft. drawdown after hrs.		
rtesian flow / g.p.m.		
nperature of water 4/1 Depth artesian flow encountered ft.	Work started Nov- 20 19 73 Complete	ed Nov-22197
CONCERNICATION.	Date well drilling machine moved off of well	
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:	
Well seal—Material used CEMENU	This well was constructed under my	direct supervision.
Well sealed from land surface toft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief	Data 14/22 107
Diameter of well bore below seal	[Signed] Orall Operator) Date 19	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 3	
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? A Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes X No	Name (Person, firm or corporation) (Type or print)	
	Address 421 Sw 6th Auc	
E	I have the	¹ d
Method of sealing strata off	[Signed] (Water Well Conta	7
Was well gravel packed? Yes No Size of gravel:	Constitute License No. 576 Date	1/22 7