WASH

NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM 10, OREGON
within 30 days from the date
of well completion.

WATER WELL REPORT 012186

STATE OF OREGON

(Please type of print)

FEB 27 1963

C 2851

State Permit No.

(1) OWNER: Name Lee Thompson	(11) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes X No If yes, by whom?			
Address PT 1	Yield: gal./min. with ft, drawdow		hrs.	
Sherwood Ore,	<u>"</u> " " " "			
(2) LOCATION OF WELL:	" "			
County Glackamas Wash, Driller's well number	Bailer test 50 gal./min. with 14 ft. drawdov	vn after	2 hrs.	
SE 4 SE 4 Section 3/4 T. 2S R. JW W.M.	Artesian flow g.p.m. Date			
Bearing and distance from section or subdivision corner	Temperature of water 52 Was a chemical analysis made? Yes X No			
	(12) WELL LOG: Diameter of well below of	oning Att	±. 000	
	Depth drilled 370 ft. Depth of completed w	asma Sur		
	Formation: Describe by color, character, size of materic	l and str	icture and	
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.			
TWDE OF WORK (A. 1)	MATERIAL	FROM	то	
TYPE OF WORK (check):	Top soil	0	1	
Well Deepening Reconditioning Abandon hdonment, describe material and procedure in Item 12.	Yellow clay sandy	1	23	
patriment, describe material and procedure in Item 12.	Brown sandy clay	23	29	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Red clay	29	33	
Domestic Industrial Municipal Rotary Driven	Brown sandy clay	_33	62	
Trrigation Test Well Cother Cable Z Jetted	Brown decomposed rock	62	88	
Dug Bored	Brown honeycomb rock (water)	88	93	
(6) CASING INSTALLED: Threaded □ Welded 🔁	Black Rock hard	93	103	
8 " Diam. from 0 ft. to 88! 7" ft. Gage .250	Grey decomposed rock	103	120	
"Diam. fromft. toft. Gage	Grey rock Hard	120	143	
"Diam. fromft. toft. Gage	Grey Honeycomb rock	143	148	
	Brown rock	148	189	
(7) PERFORATIONS: Perforated? Yes No	Grey conglomerate	189	263	
Type of perforator used	Grey rock	263	283	
Size of perforations in by in.	Soft black rock	283	284	
perforations fromft. toft.	Brown decomposed rock	284	294	
perforations fromft. toft.	Soft black rock (water)	294	301	
perforations fromft. toft.	Brown conglomerate	301	316	
periorations fromft. toft.	Gray rock Soft black rock (water)	316	357	
perforations fromft. toft.	Green conglomerate	357	368	
SCREENS: Well screen installed Yes No		3 \$ 8	370	
Macturer's Name				
Model No.			*****	
Slot size Set from ft. toft.	Work started 12/17/62 19 . Completed 2/		10	
Diam. Slot size Set from ft. to ft.	Work started 12/17/62 19 . Completed 2/17 Date well drilling machine moved off of well 2/1	11/63	19	
(9) CONSTRUCTION:		4/03	10	
	(13) PUMP:			
Well seal—Material used in seal	Manufacturer's Name		economical.	
Depth of seal	Type:	.P.		
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:			
Were any loose strata cemented off? Yes Vo Depth	" !			
Was a drive shoe used? LYes \(\subseteq \) No Was well gravel packed? \(\subseteq \) Ver \(\subseteq \) No. Size of gravel.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was well gravel packed? ☐ Yes ★ No Size of gravel:ft.		•		
The state of the s	NAME Steinmen Bros. (Type or print)			
Did any strata contain unusable water? Yes No Type of water? Depth of strata	·			
Type of water? Depth of strata Method of sealing strata off	AddressNilwaukie, Ore			
	Drilling Machine Operator's License No67			
(10) WATER LEVELS:				
Static level 51 ft. below land surface Date 2/11/63	[Signed] (Water Well Confractor)	<i>[</i>]		
Artesian pressure lbs. per square inch Date	Contractor's License No1 Date2			