G4970

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

12202 WATER WELL REPORTS 15 1967 State Well No. 2/1W-34 J

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON (Please type or print)

or were completion.	EAT STON
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name Lee Thompson	Was a pump test made? Yes No If yes, by whom?
Name Lee Thompson Address RT2 Sherwood, Ore	Yield: gal./min. with ft. drawdown after hrs.
	" " "
(2) LOCATION OF WELL;	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Ola Washington	Bailer test 30 gal./min. with 7 ft. drawdown after 2 hrs.
County Chamas priller's well number 61-66	Artesian flow g.p.m. Date
NE% SE% Section 34 T. 25 R. W.M.	Temperature of water 5/Was a chemical analysis made? Yes X No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing
1.25	Depth drilled 4// ft. Depth of completed well 4/0 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(3) TYPE OF WORK (check):	MATERIAL FROM TO
New_Well ☐ Deepening A Reconditioning ☐ Abandon ☐	Rock grey hard 347 374
If adonment, describe material and procedure in Item 12.	0 / 2 0 (# 7211 788
	Rock grey Softer 374 383
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Rock Que. hard 383 401
Domestic Industrial Municipal Rotary Driven Cable & Jetted	VIOCH Grey March 285 701
Irrigation A Test Well □ Other □ Dug □ `Bored □	arch Broken 401 410
(6) CASING INSTALLED: Threaded T Welded	VICEN VICENSER
5 1/4" Diam. from 2/87 tt. to 3/9/ ft. Gage /	
"Diam. fromft. toft. Gage	
"Diam. fromft. toft. Gage	
(7) PERFORATIONS: Perforated? W Yes \(\sigma \) No	The first 347 ft. drilled in August, 1966.
Type of perforator used CHNing Torch	Ref. to driller's well number 61-66.
Size of perforations 4 in. by 15 in.	
perforations from ft. to ft.	
perforations fromft. toft. perforations fromft. toft.	
perforations fromft. toft.	
(a) COPPENO	
(8) SCREENS: Well screen installed? ☐ Yes 🗖 No	
Manufacturer's Name	
Ty Model No.	
Diam. Slot size Set from ft. to ft.	Work started //9/67 19 Completed //25/6719
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well //30/67 19
(9) CONSTRUCTION:	(13) PUMP:
Well seal-Material used in seal See well Log 6-66	Manufacturer's Name
Depth of seal ft. Was a packer used?	Type: H.P.
Diameter of well bore to bottom of seal in.	
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:
Was a drive shoe used? 🗌 Yes 🔲 No	This well was drilled under my jurisdiction and this report is
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	NAME Steinman Bro. S (Type or print)
Did any strata contain unusable water? Yes No	
Type of water? depth of strata	Address MILWAURIE 22 Dre
Method of sealing strata off	Drilling Machine Operator's License No
(10) WATER LEVELS:	OT.
Static level \$1/ ft. below land surface Date 1/25/67	[Signed] Sllmman (Water Well Contractor)
, ,	1 9 4 4 / 2
Artesian pressure lbs. per square inch Date	Contractor's License No. Date Date 19 19