## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the 012449 STATE OF OREGON JUL 1 11973

within 30 days from the date of well completion.

(Do not write above STIME) TE ENGINEER Permit No.
SALEM OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name Albert Peterkort	County Washington Driller's well number 194		
Address 9911 S.W. Barnes Rd, Portland, Oregon	S.E. 14 NE, 14 Section 6 T. 2, S. R. 2, W. W.M.		
	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	1940's 1208 W of N.E. Corner sec. 6		
New Well Deepening . Reconditioning . Abandon .			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):			
	Depth at which water was first found		
Cable Jetted 🗆 Domestic 🗚 industrial 🗀 withhelpar 📋	Static level <b>20</b> ft. below land s	surface. Date 6//2/23	
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded   Welded 2 77   S   Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing		
6 "Diam. from 280 ft. to 450 ft. Gage 250 MA	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
DEDECD A MYONG.			
PERFORATIONS: Perforated? Y Yes   No.		<del></del>	
Type of perforator used Torch Perferated liner	MATERIAL	From To SWL	
Size of perforations in. by 34 in.	Clay - brown	0 66	
5 perforations from 310 ft. to 3.20 ft.	Clay - blue	66 /06 27	
	C/ay - brown	706 /25	
30 perforations from 400 ft. to 440 ft.	clay - brown-with rock	125 135	
(7) SCREENS: Well screen installed?   Yes No	clay - blue	135 140	
Manufacturer's Name	Clay - dark brown	170 180	
Type Model No	clay light brown	180 264	
	clay - brown clay - red - with rock	964284	
Diam. Slot size Set from ft. to ft.	nead .	384 295	
	BOCK - gray	295 346	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Corne//	Clay_ gray	346 347	
Was a pump test made? Yes \( \square\) No If yes, by whom? Pump CO.	Rock -grav	347 400	
Yield: 330 gal./min. with / 75ft. drawdown after 3 hrs.	Pack - red lara	402 407	
ried. 4.39 gai./min. with / 51t. drawdown arter 3 mis.	ROCK - 9rev	407 499	
	Rock - gray soft	499 530 27'	
" " "	ROCK - Black	520 620	
Bailer test 45 gal./min. with 6 ft. drawdown after hrs.	ROCK - bleck, 1005e folling	620 635 20	
Artesian flow g.p.m.	<u> </u>		
perature of water Depth artesian flow encountered ft.	Work started Aug 14 19 72 Completed June 12 19 23		
(9) CONSTRUCTION:	Date well drilling machine moved off of well June 19 73		
Well seal-Material used Cemant	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin.	heat knowledge and helief		
Diameter of well bore below seal	[Signed] Consulting Machine Operator Date 7/6, 19.73		
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	Drilling Machine Operator's License No. 165	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of water lbs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? Yes 🗌 No Plugs Size: location ft.	Name ABUL Barrana (Type or print)		
Did any strata contain unusable water?   Yes X No			
Type of water? depth of strata	Address 16425 Swi Hart, Beaverton, Oragon		
Method of sealing strata off	[Signed] ack Basson		
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 5	<u>//</u>	