NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be

filed with the Fig. 1931

WATER WELL REPORT ASH

STATE OF OREGON
(Please type or print)
(Do not write above this line)

	···· ·	**7	la.	1
State Well I	٧o.	o	126	 C

STATE ENGINEER, SALEM, G. GON 97310 within 30 days from the ste 0 CT 3 of well completion.

1968

State Permit No.

ALVE FINGUES.				
(1) OWNER: SALLM DREGON	(11) LOCATION OF WELL:			
Name Lyle Goodell	County Washington Driller's well nu	mber		
Address P.O. Box 23147 Tigard, Oregon	14 14 Section 6 T. 2-			
97223	·			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	1 corner		
New Well Deepening Reconditioning Abandon	Willematte Mendrian			
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):				
Rotary Driven Domestic Industrial Municipal	(12) WELL LOG: Diameter of well by	elow casing 8 inch		
Jane Jenea	Depth drilled 255 ft. Depth of comple	eted well 255 ft.		
Dug Bored I Irrigation Test Well Other	Formation: Describe color, texture, grain size a			
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratus with at least one entry for each change of form			
8" Diam, from 0 \$55 ft. to 158 ft. Gage \$ Well	in position of Static Water Level as drilling pro			
" Diam. from ft. to ft. Gage	MATERIAL	From To SWL		
" Diam, from ft. to ft. Gage	Top seil	0 3		
PERFORATIONS: Perforated? Yes No.	Yellow clay	3 8		
_ <u>2£</u> .	Blue clay with fine sar	nd 8 60		
Type of perforator used	Blue fine sand	60 105		
Size of perforations in. by in.	Blue course sand	105 110		
perforations from	Blue washed pea gravel	110 115		
perforations from ft. to ft.	Grey clay	115 125		
perforations from ft. to ft.	Red clay	125 150		
perforations from ft. to ft.	Yellow sandstone	150 210		
perforations fromft. toft.	Yellew and brown lava	210 255		
(7) SCREENS: Well screen installed? ☐ Yes ★ No	· · · ·			
Manufacturer's Name				
Type Model No,	• • • • • • • • • • • • • • • • • • • •			
Diam, Slot size Set from ft. to ft.	*			
Diam, Slot size Set from ft. to ft.		1.0		
(8) WATER LEVEL: Completed well.				
Static level 8 ft. below land surface Date 9-26-68 lian pressure lbs. per square inch Date		•		
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? 🗌 Yes 🕱 No If yes, by whom?	0.01.70	0.07.00		
Yield: gal./min. with ft. drawdown after hrs.	Work started 9-21-68 19 Complete			
" " "	Date well drilling machine moved off of well	[*] 9-23-68 ₁₉		
" " " " " " " " " " " " " " " " " " " "	Drilling Machine Operator's Certification:			
Bailer test 300 gal./min. with 60 ft. drawdown after 3 hrs.	This well was constructed under my di			
	rials used and information reported above knowledge and belief.	e are true to my best		
Artesian flow g.p.m. Date	130-111	Date 9-26, 19.68		
Temperature of water Was a chemical analysis made? ☐ Yes ▼ No	[Signed] (Drilling Machine Operator)	Date		
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	25 4		
Well seal—Material used Bentonite	Diffing Machine Operator & Dicember 1(4)			
Depth of seal 60 feet ft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdi			
Were any loose strata cemented off? 🗌 Yes 🗶 No Depth	true to the best of my knowledge and belief.			
Was a drive shoe used? 🔲 Yes 🛣 No	NAME Ralph Turner Drilling Co. (Person, firm or corporation) (Type or print)			
Did any strata contain unusable water? 🗌 Yes 🏗 No				
Type of water? depth of strata	Address Rte 1 Box 141 Hi	llabore, Oregen		
Method of sealing strata off	[Signed Statuth July	W -		
Was well gravel packed? [] Yes 📆 No Size of gravel:	(Water Well Contrac			
Gravel placed from ft. to ft.	Contractor's License No247 Date	7-26 , 19.68		