NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF OREGON JUL 9 State Well No. 25525/26-9 STATE ENGINEER, SALEM, OREGON 97310 1 9 1975 (Please type or print) SALEM, OREGON SALEM, OREGON (1) OWNER: (10) LOCATION OF WELL: 9. 2 SUTA - 2 WWM Name J & R Eakin Nursery County Washington Driller's well number Address Rt. 2 Box 210 East Section 9 25 R. 2 W Hillshoro, Oregon 97123 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well X Deepening [ Reconditioning [7] Abandon 🗀 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven [ Rotary Domestic | Industrial | Municipal | flowing Static level EXECUTE Ind surface. Date 7/7/75 Cable Jetted 🔲 Dug Irrigation 🖾 Test Well 🗌 Other Bored [ Artesian pressure lbs. per square inch. Date 7/7/75 CASING INSTALLED: Threaded [ Welded ី (12) WELL LOG: Diameter of well below casing 8.5/8... Diam. from  $\pm 1\frac{1}{2}$  ft. to 257... ft. Gage .... Depth drilled ft. Depth of completed well ..." Diam. from ...... ft. to ..... ft. Gage .... Formation: Describe color, texture, grain size and structure of materials; .." Diam. from ...... ft. to ..... ft. Gage ...... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in **PERFORATIONS:** position of Static Water Level and indicate principal water-bearing strata. Perforated? Tyes X No. Type of perforator used MATERIAL. From SWL Size of perforations in. by Brown silty clay n. perforations from \_\_\_\_\_ ft. to \_\_\_\_ ft. Brown silty sand 20 perforations from tt to Bronw silty clay w/blue-black perforations from ..... silty sand streaks 20 30 Blue silty clay-occ.black san (7) SCREENS: Well screen installed? ☐ Yes 🏝 No streaks-wood-30 4-Manufacturer's Name ..... Muddy blue-black sand, silt-wood 50 Semi-cemented black sand peagravel Diam. ..... Slot size ..... Set from ...... w/ blue clay 78 82 Diam. Slot size ...... Set from ft. to ft. Blue-grey clay-occ. sand stream-82 95 silty brown clay Drawdown is amount water level is lowered below static level (8) WELL TESTS: 700 Hard sticky brown clay 100 775 Was a pump test made? ☐ Yes ☒ No If yes, by whom? Gritty grey-brown clay 175 135 Yield: gal./min. with ft. drawdown after Hard sticky prey clay 135 hrs. 150 Hard sticky brown clay-occ. gritty 750 165 airlift Sticky orange-brown clay-occ. Bailer test gal./min. with 340 ft. drawdown after rotten rock 765 Artesian flow g.p.m. mperature of water Depth artesian flow encountered ..... 19 75 Work started 6/30 Completed Date well drilling machine moved off of well 6/30/75 (9) CONSTRUCTION: **Drilling Machine Operator's Certification:** Well seal-Material used \_\_\_\_cement, 2% Bentonite This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and ballet Well sealed from land surface to \_\_\_\_\_258 Diameter of well bore to bottom of seal  $12\frac{1}{4}$  in. Date 7/1, 19.75 Diameter of well bore below seal \_\_\_\_8 in. Number of sacks of cement used in well seal ..... Number of sacks of bentonite used in well seal \_\_\_\_\_O Brand name of bentonite \_\_\_\_\_\_\_International Gel Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is 50. true to the best of my knowledge and belief. Was a drive shoe used? Yes X No Plugs ..... Size: location ..... Name A. M. JANNSEN DRILLING CO.
(Person, firm or corporation) (Type or print) Did any strata contain unusable water? 🗌 Yes 🛣 No Type of water? Address 21075 w TV. Hwy. depth of strata Method of sealing strata off Was well gravel packed? Yes No Size of gravel: Gravel placed from \_\_\_\_\_ ft. to \_\_\_\_ Contractor's License No. ..... Date ...

# NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPOR

### STATE OF OREGON (Please type or print)

(Do not write above this line)

State Well No. -25/2 w - 9

State-Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name	County Driller's well nu	ımber	
Address	¼ ¼ Section T.	R.	W.M.
	-		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		<del></del>	
If abandonment, describe material and procedure in Item 12.			
÷	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		. ft.
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal	Static level ft. below land s	urface. Date	e
Dug	Artesian pressure lbs. per squar	e inch. Date	9
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well b		
"Diam. from	Depth drilled ft. Depth of comple	eted well	ft.
	Formation: Describe color, texture, grain size a	nd structure	of materials;
Diam, from tt. Gage	and show thickness and nature of each stratur with at least one entry for each change of format		
PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate princ		
Type of perforator used	MATERIAL	From '	To SWL
Size of perforations in. by in.			700-
	rotten rock	- 107 T	<del>100</del>
perforations from	Red-brown gritty clay & weather		
perforations fromft. toft.	brown rock Weathered brown basalt w/red-	<b>1</b> 80  2	20
perforations from ft. to ft.	brown clay	220 2	1.0
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Dirty grey-brown basalt w/occ.		
Manufacturer's Name	streaks		50
Type Model No	Black basalt		55
Diam Slot size Set from ft. to ft.	Broken brown basalt		65 WB 25
Diam Slot size Set from ft, to ft.	Hard grey brown basalt-fracture		70
	Broken black & brown basalt		82 WB 15
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Red lava & brown basalt-interbe		86
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Broken brown basalt		90
Yield: gal./min. with ft. drawdown after hrs.	Hard grey basalt-occ fractured		95
garyania waa	Vert broken grey & brown basal		10 WB 10
	Hard grey basalt occ grey-brow		TO PET ALO
" " " " " " " " " " " " " " " " " " "	basalt		20
Bailer test gal./min. with ft. drawdown after hrs.	Broken grey-brown basalt		33 WB 20
Artesian flow g.p.m.	Broken red lava & brown basalt		10 WB 20
nperature of water Depth artesian flow encountered ft.	Work started 19 Complete	ed	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	-	. 19
Well seal—Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my		
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are	true to my
Diameter of well bore below sealin.		Dete	10
Number of sacks of cement used in well seal sacks	[Signed](Drilling Machine Operator)	Date	19
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No		
Brand name of bentonite		<del></del>	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of waterlbs./100 gals.	This well was drilled under my jurisdi		his report is
Was a drive shoe used?  Yes No Plugs Size: location 1t.	true to the best of my knowledge and beli		
Did any strata contain unusable water?   No	Name (Person, firm or corporation)	(Type (	or print)
	Address		
	A SAULT COS		
Method of sealing strata off	[Signed](Water Well Contr		
Was well gravel packed?	(Water Well Contr.	actor)	
Gravel placed from ft. to ft.	Contractor's License No Date		19

# NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

#### WATER WELL REPORT

#### STATE OF OREGON

(Please type or print)

(Do not write above this line)

Page 3

	C	•		t		
			25/	1	Ç	₹
ote	W-11	Nο	25/	dw		1
auc	****	110.				

State W	en No	• :	/	 
State P	ermit	No.		 •••••

(1) OWNER:	(10) LOCATION OF WELL:	
Name	County Driller's well number	
Address	1/4 1/4 Section T. R.	W.M.
Auditos	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	bearing and distance from section of subdivision corner	
New Well □ Deepening □ Reconditioning □ Abandon □		~~~
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	•
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Driven Domestic Industrial Municipal	Static level ft. below land surface. Da	te
Cable   Jetted		
Dug	Artesian pressure lbs. per square inch. Da	
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	-
"Diam from ft. to ft. Gage	Depth drilled ft. Depth of completed well	ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structur and show thickness and nature of each stratum and aqui	e of materials;
Diam, from	with at least one entry for each change of formation. Report	each change in
(i) PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate principal water-	-bearing strata.
Type of perforator used	MATERIAL From	To SWL
	Gray-brown basalt 340 34	18
pare of portor	Gray-promi babart	
perforations from ft. to ft.		
perforations from ft. to ft.	WELL COMPLETED TO 345'	
perforations from ft. to ft.	MEDI, COMPLISIND TO 0-30	
(7) SCREENS: Well screen installed?   Yes   No		
Manufacturer's Name		
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
Diam. Stot size Set from 16. to		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☐ No If yes, by whom?		
ield: gal./min. with ft. drawdown after hrs.		
n n n n n n n n n n n n n n n n n n n		
Bailer test gal./min. with ft. drawdown after hrs.		
rtesian flow g.p.m.		
Imperature of water Depth artesian flow encountered ft.	Work started 19 Completed	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	19
그 하시 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그	Drilling Machine Operator's Certification:	
Well seal—Material used	This well was constructed under my direct a	supervision.
Well sealed from land surface toft.	Materials used and information reported above ar	e true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal in.	[Signed] Date	, 19
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.	
Number of sacks of bentonite used in well seal sacks	Diffing Macinic Operators income 110.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and	this report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.	10101010
Was a drive shoe used?  Yes No Plugs Size: location ft.		
Did any strata contain unusable water?   Yes   No	Name (Person, firm or corporation) (Type	e or print)
Type of water? depth of strata	Address	
Method of sealing strata off	[Gianad]	
Was well gravel packed? Tes No Size of gravel:	[Signed](Water Well Contractor)	
	Contractor's License No. Date	19