NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON, within 30 days from the date of well completion.

RECEIVED SEP 17 1963 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

WASH 012522

State Well No. 25/2W-9

State Permit No.

(1) OWNER:
Name C. A. Hitchcock
Address Rt 2 · Bx 170
Hillsboro, Ore

(2) LOCATION OF WELL:
County Wash Driller's well number
¼ ¼ Section T. R. W.M.
Bearing and distance from section or subdivision corner

Sec 9 T2S R2W

(3) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 209 ft. Gage 17#
5½" Diam. from 200 ft. to 225 ft. Gage 10 Ga.
" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? ☒ Yes ☐ No
Type of perforator used Torch
Size of perforations ¼ in. by 12 in.
perforations from ft. to ft.
3 per ft perforations from 215 ft. to 224 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS: Well screen installed ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Bentonite
Depth of seal 18 ft. Was a packer used? NO
Diameter of well bore to bottom of seal 8 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 35 ft. below land surface Date Sept 13-63
Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 10 gal./min. with 65' ft. drawdown after 1 hrs.
Artesian flow g.p.m. Date
Temperature of water Not ~~Not~~ a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 225 ft. Depth of completed well 225 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Brown clay	0	20
✓ silt & sand	20	60
Blue silt	60	91
✓ clay	91	103
✓ sandstone	103	108
✓ silt (~~Water~~)	108	123
✓ sand (Water)	123	133
Brown clay	133	161
Blue sand & gravel (Water)	161	164
Brown clay	164	196
~~Blue sand & gravel~~		
Sandy clay & gravel	196	210
Blue sand & gravel	210	218
Blue clay	218	225
Cemented w/ 2 gal powder		
& handfull H.T.H.		

Work started Aug 19 1963 Completed Sept 13 1963
Date well drilling machine moved off of well Sept 13 1963

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME A.V. Gaunt (Person, firm or corporation) (Type or print)
Address Aloha Ore
Drilling Machine Operator's License No. 4 & 216
[Signed] A.V. Gaunt (Water Well Contractor)
Contractor's License No. 4 Date Sept 15, 1963

(USE ADDITIONAL SHEETS IF NECESSARY)