NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT STATE OF OREGON

(Please type or print)

WATER RESOURCES DEPARTMANASH
SALEM, OREGON 97310
within 30 days from the date
of well completion. 012667

(Do not write above this line)

State Well No. 25/2	2w-16	C
1	***************************************	********
State Permit No		
deepened		

(1) OWNER:	(10) LOCATION OF WELL:	264	
Name Marvin Decker	County Washington Driller's well nu	mber 261	1 - 1
Address Rt. 4. Box 346.	34 SW 34 Section 16 T. 2-S	R. Z-W	<u> W.M.</u>
Sherwood, OR 97140	Bearing and distance from section or subdivisio	n corner	
(2) TYPE OF WORK (check):	Vanderschuers Road		
New Well Deepening Reconditioning Abandon		· ·	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		ft.
Rotary M Driven Domestic M Industrial Municipal D	Static level 120 ft. below land st	urface. Date	5/29/81
Cable	Artesian pressure lbs. per square		
Dug Bored I Irrigation I Test well Other	Altesian pressure		
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow casing	5"
" Diam. fromft. Gage	Depth drilled 115 ft. Depth of comple		5 ft.
4 " Diam. from	Formation: Describe color, texture, grain size a		materials:
ft. Gage	and show thickness and nature of each stratur	m and aquifer p	enetrated,
(a) Dabada Talong	with at least one entry for each change of format position of Static Water Level and indicate prin	ion. Report each cipal water-beari	cnange in ng strata.
(6) PERFORATIONS: Perforated? We Yes I No.		From To	SWL
of perforator used Grinding Wheel	MATERIAL		
Size of perforations in. by 8 in.	Hard Blk.&Bron Basalt	150 180	
60 perforations from 60 ft. to 265 ft.	Hard Gray Basalt	180 210	-
perforations from ft. to ft.	Hard Blk & Brwn. Broken	210 26	d:
perforations from ft. to ft.	Basalt	210 20.	<u> </u>
(7) SCREENS: Well screen installed? Yes No			
• •			
Manufacturer's Name Type Model No			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED		
Was a pump test made? ☐ Yes [₹No If yes, by whom?	JUN 2 5 1981		
Yield: gal./min. with ft. drawdown after hrs.		 	
"Airlifted 85 "GPM from 265" after 1 hr.	WATER RESOURCES DEPT		
" " "	SALEM. OREGON	 	
Bailer test gal./min. with ft. drawdown after hrs.	<u> </u>	 	-
			
Artesian flow g.p.m.	5/2C/01 to Complete	F /20 /01	19
Temperature of water 56 Depth artesian flow encountered ft.		ed 5/29/81	
CONSTRUCTION:	Date well drilling machine moved off of well	5/29/81	19
Well seal—Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct supe	rvision. ie to mv
Diameter of well bore to bottom of seal in.	hest knowledge and helieft \ \ \	. (_
Diameter of well bore below seal in.	[Signed] Leurus X Labour	Date 6 23	19.5
Number of sacks of cement used in well seal sacks			
How was cement grout placed?	Drilling Machine Operator's License No.	TAO#	
	Water Well Contractor's Certification:		
	This well was drilled under my jurisd	liation and this	report is
	true to the best of my knowledge and be	lief.	TOPOTE 19
Was a drive shoe used? \square Yes	Name Arrow Drilling		
Did any strata contain unusable water? 🗌 Yes 🔯 No	(Person film or comoration)	(Type or p	
Type of water? depth of strata	Addres 729 N. Malin, Newb	erg. OR	97132
Method of sealing strata off	Leanier & Country & Chamier	MÐ	
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	(Water Well Cont	1 1 - 2	^ .
Gravel placed from ft. to ft.	Contractor's License No. 645 Date	6/23	, 19.8.(
Graver praced Hom		- ' \	,