The original and first copy of this report are to be filed with the NOV 6 1969

STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97316 ENGINEER case type or print) within 30 days from the date N IE ENGINEER case type or print) of well completion. SALEM. OREGON

State Permit No. ...

(1) OWNER:	(11) LOCATION OF WELL:			
Name CRE, & Wash, Lumber Co.	County WASA Driller's well n	umber	15%	
Address 1/23 SW Yamhill, PorTland OFB	NE 14 NW14 Section 26 T. 25		aw/	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner		

New Well Depening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well	below ca	sing 6	u
Cable	Depth drilled 230 ft. Depth of comp.			ø ft.
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Formation: Describe color, texture, grain size			
(5) CASING INSTALLED: Threaded Welded W	and show thickness and nature of each stratu	ım and a	aquifer pe	netrated,
6 " Diam. from 6 ft. to 117 ft. Gage 250	with at least one entry for each change of form in position of Static Water Level as drilling pr			
		From	То	SWL
ft. Gage				SWE
	Brown Soil	0	ダン	·
(5) PERFORATIONS: Perforated? Yes No.	Red Chay	2		
Type of perforator used	Brown Stale	52	108	
Size of perforations in. by in.	GRAY Broken BASA/T	108	152	<u> </u>
perforations from ft. to ft.	Red Porous BASAVT	152	164	<u> </u>
perforations from ft. to ft.	HAVO GRAY BASALT	164	210	
perforations fromft. toft.	GRAY, Drown Broken BASAIT	2/0	292	
perforations from ft. to ft.	Brown yellow Poras BASOIT	292	302	
perforations fromft. toft.	Hard GRAY BASALT	302	336	
periorations from the to the first transfer of the first transfer	GRAY Brown Broken Brant	336	426	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	HARD GRAY BASAIT	426	439	
Manufacturer's Name	Brown GRAY BUCKON BASALT	439	485	
Type Model No.	HAND GRAY BASALT	485	527	<u>, </u>
Diam Slot size Set from ft. to ft.	Brown Polous Basa/T	527	548	-
Diam. Slot size Set from ft. to ft.	HAND GRAY BASALT	548	563	
	Brown Porous BASALT	563	570	
(8) WATER LEVEL: Completed well.	HAND GRAY BASALT	570	610	
tt. below land surface Date 10-23-69	BLOWN GRAY POLOUS BASA/MINITER	610	622	395
Artesian pressure lbs. per square inch Date	HAIR GRAY BASALT	622	630	
			ļ	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level		<u></u>		ļ
Was a pump test made? Yes \(\) No If yes, by whom? OPera Ter		<u> </u>		
1: 30 gal./min. with 235 ft. drawdown after 2 hrs.	Work started 10-20 1969 Complete	ed /C	-23	1969
" " " "	Date well drilling machine moved off of well	0-2	3	1969
" " "	Drilling Machine Operator's Certification:			
Bailer test gal./min. with ft. drawdown after hrs	This well was constructed under my di	irect sur	ervision.	Mate-
A	rials used and information reported above	ve are î	true to r	ny best
Artesian flow g.p.m. Date	knowledge and belief.		•	
Temperature of water 52 ° Was a chemical analysis made? ☐ Yes ☑ No	[Signed] Willing Machine Operator)	Date	10-23	3, 19. 6.9
(10) CONSTRUCTION:				:
Well seal-Material used Bentonite Cuttings	Drilling Machine Operator's License No	\\$ <i>U</i> \	<u>ح</u>	
Day 117	Water Wall Control of the Alexander			***************************************
Diameter of well bore to bottom of seal 9 in.	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Were any loose strata cemented off? Yes No Depth	NAME BAS Drilling Co.			
Was a drive shoe used? ☐ Yes ☒ No	(Person, firm or corporation)	(Тур	e or print)	/
Did any strata contain unusable water? Yes No	Address TT 3 Box 27/A	Sh	Brwon	done
Type of water? depth of strata			7.2.2.2	∼ سائنگلاسولىت
Method of sealing strata off	[Signed] Daymond A	Sore	lon_	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contract	tor)		
Gravel placed fromft. toft.	Contractor's License No. 404 Date	10-=	, . ?	10/9
It.	Commacion a License No A.S Date/	<u>ex</u>	~ ;	19125.4."