NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED JUN 18 1973 STATE ENGINEER SALEM, OREGON

WASH 013522 bd

State Well No. 2S/3W-14

State Permit No.

6-7/23

(1) OWNER:
Name Stanley W Beerli
Address P.O Box 272, Beaverton Ore

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 62 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? Operator
Yield: 40 gal./min. with 68 ft. drawdown after 2 hrs.
" " "
" " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 54° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 62 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 12 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Wash Driller's well number 342
SE ¼ NW ¼ Section 14 T. 2S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 276-288 ft.
Static level 136 ft. below land surface. Date 6-1-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 305 ft. Depth of completed well 305 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Brown Soil	0	2	
Brown Clay	2	28	
Gray Shale	28	52	
Medium Hard Gray Basalt	52	94	
Brown + Gray Basalt	94	96	
Medium Hard Gray Basalt	96	106	
Brown + Gray Basalt	106	118	
Gray Basalt + Clay Seams	118	128	
Hard Gray Basalt	128	204	
Brown + Gray Basalt	204	222	
Hard Gray Basalt	222	276	
Brown, Yellow Porous Basalt (water)	276	288	136
Hard Gray Basalt	288	305	

Work started 5-31 19 73 Completed 6-1 19 73
Date well drilling machine moved off of well 6-1 19 73

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Raymond A. Borchers Date 6-1, 19 73
(Drilling Machine Operator)
Drilling Machine Operator's License No. 305

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Ray Borchers - Well Drilling
(Person, firm or corporation) (Type or print)
Address RT3, Box 271A Sherwood, Ore.
[Signed] Raymond A. Borchers
(Water Well Contractor)
Contractor's License No. 404 Date 6-1, 19 73

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119