The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT WASK

(Please type or print)
(Do not write above this line) 13541

¥	State 1	37e11	Ma	25	13	رر)-	-2	4
	State	as CTT	140.	4	1			

(Please type or print)

State	Well No.	The second secon	
State	Permit No.		

(1) OWNER:	(10) LOCATION OF WELL:	
Name ARTTUR FROWN	County WASHINGTON Driller's well nur	nber
Address RT 4 1 BOX 274 E	56 % S. % Section 24 T. 25	R. JU) W.M.
Address	Bearing and distance from section or subdivision	
(2) TYPE OF WORK (check):		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	<b>II.</b>
	1	ft.
(0) ====	Depth at which water was first found	mine Date #4/8/21
Rotary Moriven Domestic Manicipal Domestic Municipal Domestic	Static level 50 ft. below land st	
Dug	Artesian pressure Ibs. per square	men. Date
CASING INSTALLED: Threaded Welded Grand Welded Grand Tt. to 27 ft. Gage 1350	(12) WELL LOG: Diameter of well be Depth drilled 16 of ft. Depth of comple Formation: Describe color, texture, grain size 4	ted well / RO tt.
Diam. from ft. to ft. Gage Perforated? Yes No.	and show thickness and nature of each stratum with at least one entry for each change of format position of Static Water Level and indicate prince	ion. Report each change in
	MATERIAL	From To SWL
T. s of perforator used	CLAY RADWA	0 40
Size of perforations in. by in.	CLAY BROWN BOULDERS	40 55
perforations from	BASALT BANKEN DECOMPOSED	2 3 0/2
perforations fromft. toft.	BASALT, BLACK, FRACTURE	180 120
perforations from ft. to ft.	RASALT, BLACK, HARD	120 123
(7) SCREENS: Well screen installed?   Yes Y No	RASALT BAWSEN	173 190 50
Manufacturer's Name		
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made?   Yes   No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		<del>                                     </del>
" "		
" "		
Bailer test 30 gal./min. with ft. drawdown after hrs.		
Date to a		
Artesian flow g.p.m.	Work started 4/1/24/ 19 Complet	ed 4/2/7# 19
erature of water Depth artesian flow encountered ft.	Date well drilling machine moved off of well	4/2/2019
(5) CONSTRUCTION:		1111
Well seal-Material used CEMFIT GROUT	Drilling Machine Operator's Certification This well was constructed under my	direct supervision.
Well sealed from land surface toft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of seal	best knowledge and helief	n 11/2 7V
Diameter of well bore below seal	Dailling Machine Operators	Date
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.	877
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	· ·
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	liction and this report is
of water	true to the best of my knowledge, and be	elling Ina.
Was a drive shoe used?   Yes   No Plugs Size: location ft	Name (Person, firm or corporation)	(Type or print)
Did any strata contain unusable water?   Yes No	Address 421 SW 6TH NUE, B	Type or print)
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed] (Water Well Con	tractor)
Was well gravel packed? [] Yes [X] No Size of gravel:	= \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	11-2-
Gravel placed from ft. to ft.	Contractor's License No 74. Date	