

RECEIVED

WASH 013558

2h/4w-9da

STATE OF OREGON WATER WELL REPORT (as required by ORS 517.785)

PLEASE TYPE or PRINT IN INK

(for official use only)

WATER RESOURCES DEPT

(1) OWNER:

Name: State of Oregon Hwy. Dept. Address: Rt 1 Box 298 City: Banks State: OR 97106

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

(3) TYPE OF WELL:

Rotary Air [x] Driven [ ] Rotary Mud [ ] Dug [ ] Cable [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [x] Industrial [ ] Municipal [ ] Thermal [ ] Irrigation [ ] Withdrawal [ ] Reinjection [ ] Other: Piezometric [ ] Grounding [ ] Test [ ]

(5) CASING INSTALLED:

Steel Threaded [x] Plastic Welded [x] 6" Diam. from +1 ft. to 124 ft. Gauge 2.50

LINER INSTALLED:

Steel Threaded [ ] Plastic Welded [x] 4" Diam. from 5 ft. to 300 ft. Gauge 160 p.s.d.

(6) PERFORATIONS:

Perforated? [x] Yes [ ] No Size of perforations 1/2 in. by 1/2 in. 60 perforations from 140 ft. to 280 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No Manufacturer's Name: Type: Model No: Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [ ] Yes [x] No If yes, by whom? Air test 7 1/2 gal./min. with drill stem at 240 ft. 1 hrs. Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes [ ] No [x] Well seal—Material used Cement Well sealed from land surface to 120 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Amount of sealing material 22 sacks [x] pounds [ ] How was cement grout placed? Pumped Was pump installed? No Type HP Depth ft. Was a drive shoe used? [x] Yes [ ] No Plugs Size: location ft. Did any strata contain unusable water? [ ] Yes [x] No Type of Water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County: Wash NE 1/4 SE 1/4 of Section 9 of Township 2N Range 4W WM. Tax Lot Lot Block Subdivision

MAILING ADDRESS OF WELL (or nearest address):

Rt 1 Box 298 Banks OR 97106

(11) WATER LEVEL OF COMPLETED WELL:

Depth at which water was first found 140 ft. Static level 15 ft. below land surface. Date 4-2-86 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 Depth drilled 300 ft. Depth of completed well 300 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Brn Soil (0-2), Brn clay - Baldus (2-35), Blue sandstone (35-140), Fractured sandstone (140-160, 15), Blue sandstone (160-300, 15)

Date work started 4-1-86 / completed 4-2-86 Date well drilling machine moved off of well 4-2-1986

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date 19

(bonded) Water Well Constructor Certification:

Bond 32740 Issued by: Ore auto dns (Surety Company Name) On behalf of Joseph Trussell (type or print name of Water Well Constructor)

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:

(Signed) Joseph Trussell (Water Well Constructor) (Dated) 4-2-86

NOTICE TO WATER WELL CONSTRUCTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP\*46866-690