STATE OF OREGON
WATER WELL REPORTATER RESOURCES DEPT.
(as required by ORS 537.766)
SALEM, OREGON

(as required by ORS 537.765)	(BIART ONED) #
(1) OWNER: Well Number:	(9) LOCATION OF WELL by legal description:
Name ROCKFORD REGULA	County WASH Latitude Longitude
Address 5010 N.W. SEWELL RD	Township 1 No Range 2 W,
City HILLS BORO State OR Zip 97124	Section
(2) TYPE OF WORK:	Tax Lot 0/03 Lot Block Subdivision
New Well Deepen Recondition Abandon	Street Address of Well (or nearest address)
(3) DRILL METHOD	
☐ Rotary Air ☐ Rotary Mud     Cable	(10) STAŢIC WATER LEVEL:
□ Other	22 ft. below land surface. Date OCT 29
(4) PROPOSED USE:	Artesian pressure lb. per square inch. Date
Domestic Community Industrial Irrigation	(11) WATER BEARING ZONES:
☐ Thermal ☐ Injection ☐ Other	(11) WAIER BEARING ZONES:
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found
Special Construction approval Yes No Depth of Completed Well 130	t. From To Estimated Flow Rate SWL
Yes No	125 130 10 GPM 22
Explosives used	- 4
HOLE SEAL Amount	
Diameter From To Material From To sacks or pounds $10^{\circ\prime\prime}$ $10^{\circ\prime\prime}$ $18^{\circ\prime\prime}$ $18^{\circ\prime\prime}$ $18^{\circ\prime\prime}$ $18^{\circ\prime\prime}$ $18^{\circ\prime\prime}$ $18^{\circ\prime\prime}$	
6" 0 130 BENT: 0 18 350	(12) WELL LOG: Ground elevation Aprex 230
6 0 130	
	Material From To SWL
How was seal placed: Method A B C D E	
Mother Poured DRY	DARK BROWN Clay 1 5 BROWN SANDY Clay 5 20
Backfill placed fromft. toft. Material	- Rive grey sauny clay 20 35
Gravel placed fromft. toft. Size of gravel	Blue grey Clay Broken Basett 35 40
	Bive grey SILTY Clay 40 45
(6) CASING/LINER:  Diameter From To Gauge Steel Plastic Welded Threade	
Casing: Diameter From To Gauge Steel Plastic Welded Threade	light Brown Clay 53 63
	MEDIUM hard redish brown 63 66
	SOFY redish brain clay 66 85
	Blue grey Clay to brown 85 103
Liner: 5"  30   1/3   160	Rive grey with wood 103 108
	Blue grey clay sticky line 120
Final location of shoe(s) 128-9"	Blue grey Sandy Clay 120 130 22'
(7) PERFORATIONS/SCREENS;	
Perforations Method Circular Saw	
Screens Type Material	
Slot Tele/pipe	
From To size Number Diameter size Casing Liner	
129 125 5x 1/20	
	24 2 4 2 4
	Date started 24 Oct Completed 29 Oct
	- (unbonded) Water Well Constructor Certification:
(8) WELL TESTS: Minimum testing time is 1 hour Flowing	I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon well construction
☐ Pump 🕱 Bailer ☐ Air ☐ Artesian	standards. Materials used and information reported above are true to my best
Yield gal/min Drawdown Drill stem at Time	knowledge and belief.
9+6Pm 9t 75' 1hr.	Thatial Colomber 1538
	Signed DATIN Date 6C1 31
	(bonded) Water Well Constructor Certification:
Temperature of water 53 Depth Artesian Flow Found	. I accept responsibility for the construction, alteration, or abandonment
Was a water analysis done? Yes By whom	work performed on this well during the construction dates reported above. all work performed during this time is in compliance with Oregon well
Did any strata contain water not suitable for intended use?   Too little	construction standards. This report is true to the best of my knowledge and
□ Salty □ Muddy □ Odor □ Colored □ Other	_ belief. WWC Number
Depth of strata:	Signed And A Miles Date 5/ 304 /990