$\frac{2}{2} \frac{1}{2} \frac{1}$

WASH RECEI	VED /8/3/	17 h	
STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765) JUN 14	1993 (START CARD) # 54462		
WATER RESOU			
(1) OWNER: Well Number SALFM ON SALFM	County ASHINGTON Latitude Longitude		
Address 20580 SW WESTSIDE STREET	Township 1S N or S. Range 3W E	or W. WM.	
City ALOHA State OR Zip 97007			
(2) TYPE OF WORK:	Tax Lot 00600 Lot Block Subdivision		
New Well Deepen Recondition Abandon	andon Street Address of Well (or nearest address) 34120 SW TV HWY		
) DRILL METHOD: HILLSBORO, OR 9/123			
Rotary Air 🖾 Rotary Mud 🗌 Cable	(10) STATIC WATER LEVEL:	06/04/02	
Other		06/04/93	
(4) PROPOSED USE:	Artesian pressure lb. per square inch. Date		
☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation	(II) WATER BEARING ZONES:		
☐ Thermal ☐ Injection ☐ Other	Depth at which water was first found 101		
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found		
Special Construction approval Yes No Depth of Completed Well 125 ft.	From To Estimated Flow R	ate SWL	
Explosives used Yes Ano Type Amount	101 121 90 gpm		
HOLE SEAL Amount	101 121 70 891		
Diameter From To Material From To sacks or pounds 12 0 125 Cement⋛ 0 40 20 sks.			
Drill gel 40 65			
Cement & gel 65 85 10 sks.	(12) WELL LOG:		
Sand Pack 85 125 22 sks.	Ground elevation		
How was seal placed: Method A B XX C D E			
Other	Material From	To SWL	
Backfill placed from ft. to ft. Material	Soft brown silty clay 0	28	
Gravel placed from 85 ft. to 125 ft. Size of gravel sand 1-C	Soft gray-brown silty clay 28	39	
(6) CASING/LINER:	Soft gray silty clay w/sand 39	88	
Diameter From To Gauge Steel Plastic Welded Threaded	seams		
Casing: 8 + 2 101 250 X - X	Sticky gray & blue-gray clay 88	96	
8 121 125 250 X	Sticky gray silty clay 96 Medium sand & fine gravel 101	101 110 25	
	Gravel & coarse sand 110	121 25	
	Sticky gray clay 121	125	
Liner:	S C L C L C L C L C L C L C L C L C L C		
Final location of shoe(s)			
(7) PERFORATIONS/SCREENS:			
Perforations Method			
X Screens Type SS WIREWOUNWaterial STEEL			
Slot Tele/pipe			
From To size Number Diameter size Casing Liner 101 111 .020 .050 8 pipe ⊠ □			
101 111 .020050 8 pipe X			
111 121 1030 0 page M			
(8) WELL TESTS: Minimum testing time is 1 hour			
Flowing	Date started 05/20/93 Completed 06	/04/93	
Pump Bailer X Air Artesian	(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or abandon-		
Yield gal/min Drawdown Drill stem at Time	ment of this well is in compliance with Oregon well construction, after at	ion, or abandon- idards. Materials	
	used and information reported above are true to my best knowledg	e and belief.	
90 65 1 hr.	WWC Nu	mber <u>1492</u>	
	Signed Mel Bucky Date 06		
	(bonded) Water Well Constructor Certification:		
Temperature of Water 54°F Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work per-			
Wes a water analysis done? Ves Ry whom formed on this well during the construction dates reported above. All work performed			
Did any strata contain water not suitable for intended use? Too little	during this time is in compliance with Oregon well construction stand is true to the best of my knowledge and belief.		
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other	WWC N	ımber <u>1266</u>	
Depth of strata:	Signed Date 06	/09/93	

Depth of strata: