WATER WELL REPORT SEP - 8 1993
(as required by ORS 537765)

(as required by Oks 557.70 WATER RESOURCES DE.	(START CARD) #)
SALEM, OREGON		
1) OWNER: Well Number	Well Number (9) LOCATION OF WELL by legal description:	
Vame JOHN PAULSON	County WASHINGTON attitude Lo	
Address 4087 SE SPRING	Township 1S N or S. Range 2W	E or W. WM.
City HILLSBORO State OR Zip 97123	Section <u>30</u> <u>NE</u> ¼ <u>NW</u>	
2) TYPE OF WORK: Tax Lot 308 Lot Block Subdivision		
New Well Deepen Recondition Abandon Street Address of Well (or nearest address) BURKHALTER RD		
3) DRILL METHOD:	HTLLSBORO, OR	
X Rotary Air Rotary Mud Cable (10) STATIC WATER LEVEL:		
X Rotary Air Rotary Mud Cable		5 00/01/00
Other	67 ft. below land surface. Date 08/31/93	
4) PROPOSED USE: Artesian pressure lb. per square inch. Date		
Domestic Community Industrial Irrigation	(11) WATER BEARING ZONES:	
☐ Thermal ☐ Injection ☐ Other		
5) BORE HOLE CONSTRUCTION:	Depth at which water was first found169	
Special Construction approval \square Yes \overline{X} No Depth of Completed Well 192 ft.		
Explosives used Yes No Type Amount	From To Estimate	ed Flow Rate SWL
	169 185 27	gpm 67
HOLE SEAL Amount Diameter From To Material From To sacks or pounds		OF
10 0 24 Cement 0 24		
8 24 79 Cement 24 79 16 sks.		
6 79 192	(10)	
0 79 192	(12) WELL LOG:	
	Ground elevation	
How was seal placed: Method \square A \square B \square C \square D \square E		······
Other	Material	From To SWL
Backfill placed from ft. to ft. Material	Topsoil	0 1
Gravel placed from ft. to ft. Size of gravel	Brown clay	1 19
6) CASING/LINER:	Soft gray-brown basalt with	19 25
Diameter From To Gauge Steel Plastic Welded Threaded	decomp. streaks	
Casing: 6" +1 79 250 X	Decomp.red-brown basalt	25 40
	Firm gray-brown basalt	40 75
	Hard gray basalt	75 97
	G-ft 1 1	
	Soft brown basalt	
Liner:		104 121
		121 154
Final location of shoe(s)	soft interbeds	
(7) PERFORATIONS/SCREENS:		154 169
Perforations Method	Soft gray-brown basalt	169 185 67
Screens Type Material		185 192
Slot Hele/pipe		
From To size Number Diameter size Casing Liner		
(8) WELL TESTS: Minimum testing time is 1 hour		
Flowing	Date started08/30/93 Completed _0	8/31/93
Pump Bailer Air Artesian	(unbonded) Water Well Constructor Certification:	
Viold got/min Drowdown Duill stom of Time	I certify that the work I performed on the construction	
Yield gal/min Drawdown Drill stem at Time	ment of this well is in compliance with Oregon well constru	
27 190 1 hr.	used and information reported above are true to my best	knowledge and belief.
27 150 "	V	VWC Number
20 . 100 "	ł	ate
Temperature of Water58 ° F Depth Artesian Flow Found	(bonded) Water Well Constructor Certification:	
	I accept responsibility for the construction, alteration, of formed on this well during the construction dates reported a	
Was a water analysis done? X Yes By whom AMJ	during this time is in compliance with Oregon well construc	
Did any strata contain water not suitable for intended use? Too little		-
Salty Muddy Odor Colored Other	1 . / 2	WWC Number 1266

Depth of strata: _