

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 2N-2W-21C

State Permit No. _____

(1) OWNER:

Name Bill Peterson
Address 844 SE 37th
Hillsboro, OR 97123

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Jetted ☐ Bored ☐
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(4) PROPOSED USE (check):

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
6" Diam. from +1 ft. to 32 ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used _____

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name _____
Type _____ Model No. _____
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Is a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Air 60 gal./min. with 40 ft. drawdown after 1 hrs.
Artesian flow g.p.m.

Temperature of water 59 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout
Well sealed from land surface to 32 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 10 sacks
How was cement grout placed? Pressure grouted

Was a drive shoe used? ☒ Yes ☐ No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? _____ depth of strata _____

Method of sealing strata off _____

Was well gravel packed? ☐ Yes ☒ No Size of gravel: _____
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Washington Driller's well number _____
1/4 S.W. 1/4 Section 21 T. 2N R. 2W W.M.
Bearing and distance from section or subdivision corner _____

(11) WATER LEVEL: Completed well.

Depth at which water was first found 74 ft.
Static level 36 ft. below land surface. Date 8/27/80
Artesian pressure lbs. per square inch. Date _____

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 80 ft. Depth of completed well 80 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown Clay / gravel	2	8	
Brown Sandy Clay	8	20	
Broken Rock	20	26	
Conglomerate	26	29	
Basalt	29	39	
Weathered Basalt	39	58	
Sandstone	58	62	
Blue Basalt	62	73	
Fractured Basalt	73	80	H2O

RECEIVED

JAN 20 1981

WATER RESOURCES DEPT
SALEM, OREGON

Work started 8/27/80 19 Completed 8/27/80 19
Date well drilling machine moved off of well 8/27/80 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Harshul R. Halcy Date 9/15/80, 19____
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1144

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Submersible Pump & Drilling Co.
(Person, firm or corporation) (Type or print)

Address Rt. 1, Box 703 Hillsboro, Ore.

[Signed] Harshul R. Halcy
(Water Well Contractor)

Contractor's License No. 669 Date 9/15/80, 19____