NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT E IVE

STATE ENGINEER, SALEM, OREGON 97310 WASH within 30 days from the date of well completion.

(Please type opring TE ENGINEED Permit No.
(Do not write above this lineEM OREGON:

	 			
(1) OWNER:	(10) LOCATION OF WELL:			
Name West Oregon Nursery	County Washington Driller's well number			
Address 3550 N. W. Saltzman Road	34 34 Section 28 T. 1 N R. 1 W. W.M.			
Portland, Oregon 97229	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):				
New Well 🔀 Deepening 🗌 Reconditioning 🗍 Abandon 🗍				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL Completed w			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.			
	Depth at which water was first found 65			ft.
Rotary 🔀 Driven 🗌 - Domestic 🗌 Industrial 🗎 Municipal 🗎	Static level 6 ft. below land s	urface. Date	<u> 10/2</u>	<u> 25/72 </u>
Dug 🛮 Bored 🗀 Irrigation 🛱 Test Well 🗀 Other 🖸	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded □ Welded № 8 " Diam. from 0 ft. to 50 ft. Gage	(12) WELL LOG: Diameter of well below casing			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-l	bearing	strata.
Type of perforator used	MATERIAL			SWL
Size of perforations in. by in.	Top soil	0 2	2 17	 -
perforations from ft. to ft.	Brown clay	17	29	
perforations from ft. to ft.	Blue clay	29	36	
perforations from ft. to ft.	Brown clay	36	44	·
(7) SCREENS: Well screen installed? Yes M No	Decomposed & clay	1411	65	
• • • • • • • • • • • • • • • • • • • •	Brown & gray rock	65		75 gpm
Manufacturer's Name	Broken gray rock		103	17 gpm
Type Model No,	Broken Brn & gray-perforated		146	
Diam. Slot size Set from ft.	Broken brown & gray rock		212	
Diam. Slot size Set from ft. to ft.	Hard gray rock		242	
(8) WELL TESTS: Drawdown is amount water level is	Broken brown & gray rock	1 1	267	
Towered below static lever	Hard gray rock	•	276	
Was a pump test made? Yes No If yes, by whom?	Broken gray rock Hard gray rock	4 1	284	
Yield: gal./min. with ft. drawdown after hrs.	Broken gray rock		- 1	62 gpm
" "	Hard gray rock	1 71	310	<u> </u>
" " "		/	-	
airlift Bailer test 137 gal./min. with 294 ft. drawdown after 2 hrs.	The second secon		-	 ·
		 		
Artesian flow g.p.m.	70/00/70	- 70/05	/70	
perature of water Depth artesian flow encountered ft.	Work started 10/23/72 19 Complete		/ 14	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10/25/	72	19
Well seal—Material used	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signetif Machine Operator] Drilling Machine Operator's License No. 235			
Number of sacks of bentonite used in well seal sacks	Diffing Machine Operator's Dicense No.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons		iction and :	thig ret	nort is
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name A. M. Jannsen Drilling Co) .		
Did any strata contain unusable water? 🗌 Yes 📉 No	(Person firm or cornoration)	(Type	or print)	na Omor
Type of water? depth of strata	Address 21075 S.W. Tualatin Val.	rea uma	TOTA	OT. G
Method of sealing strata off	Isimot Williams Ill	rende	'n	
Was well gravel packed? ☐ Yes 戊 No Size of gravel:	[Signed] (Water Well Control			
Gravel placed from	Contractor's License No. 79 Date 1	1/6/72		19