The original and first copy of this report are to the filed with the MAY 30 1972 STATE OF OREGON

filed with the MAY 30 19/2 STATE OF OREGON STATE ENGINEER, SALEM, OREGON STATE IN CONTROL OF Well completion. SALEM OF (b) not write above this line)

State Well No.

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Robert A. Johnson	County Washington Driller's well number
Address 575 S.W. Soring Lane Portland, Or.	34 34 Section Q T. N R. Z. W. M.
97225	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Bottling direct district and bottling out the second of th
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	l ` '
Rotows El Driven D	Depth at which water was first found 95 ft.
Cable Jetted Domestic industrial Municipal	Static level 6 5 ft. below land surface. Date 5/22/72
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
Threaded Welded	(12) WELL LOG: Diameter of well below casing 6. Depth drilled 2/5 ft. Depth of completed well 2/5 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsoil 62
perforations from ft. to ft.	rellow Clay Z 8
perforations from ft. to ft.	Red Clay 8 25
perforations from ft. to ft.	Yellow Clay 25 95
(T) GGDTT1G	Brown Clay 95 108
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Brown Medium Rock 108 115
Manufacturer's Name	Blue Medium Rock 115 135
Type Model No.	Brown Lava Rock 135 155
Diam. Slot size Set from ft.	Blue Medium Rock 155 165
<u>Diam.</u> Slot size Set from ft. to ft.	Brown Lava Rock 165 180
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Blue Hard Rock 180 184 Black Lava Rock 184 186
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	Blue Hard + soft layers 186 213
Yield: gal./min. with ft. drawdown after hrs.	Brown Medium Rock 213 215
<i>"</i> " " " "	
" " " " " " "	
Bailer test 70 gal./min. with/00 ft. drawdown after / hrs.	
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encountered	Work started 5/22 1972 Completed 5/22 1972
inperature of water Depart artesian now encountered	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5/22 1972
Well seal—Material used Cement Well sealed from land surface to 119 ft. Diameter of well bore to bottom of seal 9 in. Diameter of well bore below seal 5 in. Number of sacks of cement used in well seal 4 sacks	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Date 5/26, 1977 [Drilling Machine Operator) Drilling Machine Operator's License No. 254
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name Kalph Turner Drilling Company (Type or print)
Type of water? depth of strata	Address Rte 1 Box 141 Hillsbord, Or. 97123
	21.11
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? Yes No Size of gravel:	Contractor's License No. 247 Date 247 5/26 1972
March March 1900 If TO II	- Communication of Lifetime Division Light A. T. L. C.