NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

 k_{I}

State Well No	1W/2W-3
---------------	---------

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVE B not write above this line)

-Gri
1 Pig
W/18
ho.
- J

State Permit No.

(1) OWNER: QCT 3 1 1975	(10) LOCATION OF WELL:		
Name Stanley R. Pearlman	County Washington Driller's well number		
Address Rte 1 BowAFER HESQUEGES, DEFERON	14 14 Section 3 T. 1-N		
SALEM, OREGON	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):	Drotting date dispersion in the second	·	
New Well		7 70	
If abandonment, describe material and procedure in Item 12.	(11) THATTED LEVEL. Completed W		
	(11) WATER LEVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was instituted		
Rotary 15 Driven Domestic K Industrial Municipal Cable Deficiency	Static level 59 ft. below land s	urface. Date 10-27-75	
Cable	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded Welded		pelow casing6	
6 "Diam. from 0 ft. to 202 ft. Gage 280	Depth drilled 363 ft. Depth of compl	eted well 363 ft.	
	Formation: Describe color, texture, grain size a	and structure of materials;	
ft. toft, Gage	and show thickness and nature of each stratus with at least one entry for each change of forma	n and aquifer penetrated,	
DEDUCTION A MICONG.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
PERFORATIONS: Perforated? Yes No.	MATERIAL	From To SWL	
Type of perforator used	MATERIAL		
Size of perforations in. by in.	Top soil	0 2	
perforations from ft. to ft.	Brown clay	2 38	
perforations from ft. to ft.	Blue clay	38 47	
perforations from ft. to ft.	Brown clay	47 108	
	Red clay	108 196	
(7) SCREENS: Well screen installed? Yes No	Blue med. rock	196 235	
Manufacturer's Name	Brown lava rock	235 241	
Type Model No	Blue med. rock	241 290	
Diam Slot size Set from ft. to ft.	Brown lava rock	290 298	
Diam. Slot size Set from ft. to ft.	Blue med. rock	298 305	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black lava rock	305 320	
(8) WELL TESTS: lowered below static level	Blue med. rock	320 342	
Was a pump test made? Yes XXNo If yes, by whom?	Black and brown lava	342 351	
Yield: gal./min. with ft. drawdown after hrs.	Blue med. rock	351 363	
" "			
" " "			
air KENET test 45 gal./min. with 284ft. drawdown after 1 hrs.			
Artesian flow g.p.m.	10 25 75 to Comple	ted 10-27-7519	
nperature of water Depth artesian flow encountered ft.	Work started 10-25-75 19 Comple		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10-23-75 19	
• •	Drilling Machine Operator's Certification	:	
Well seal-Material usedCement	This well was constructed under my Materials used and information reported	direct supervision.	
Well sealed from land surface to	best knowledge and belief.	Labove are wide to may	
Diameter of well bore to bottom of seal	[Giornal And and July	Date 10-28-759	
Diameter of well bore below seal	(Drilling Machine Operator)		
Number of sacks of cement used in well seal 20sacks	Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my juris true to the best of my knowledge and be	diction and this report is	
Was a drive shoe used? ☐ Yes XXNo Plugs Size: location ft.		,	
Did any strata contain unusable water? Yes No	Name Ralph Turner Drilling	(Type or print)	
	Address Rte 1 Box 141 Hills	sboro, Oregon	
Type of water? depth of strata	(D) 1 M	<u></u>	
Method of sealing strata off	[Signed] (Water Well Cor	MATULE TOTAL	
Was well gravel packed? ☐ Yes 🙀 No Size of gravel:			
Gravel placed from ft. to ft.	Contractor's License No247 Date	I.U=と0=イラ, 19	