The original and first copy of this report are to be filed with the

Gravel placed from

..... ft. to

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

JUL 1 5 1994 tate Well No. RECEIVED

... (Please type or print)

(Do not write above this IWATER RESOURCES State Permit No. AUG 2 2 199

Of Wen completion.	SALEM, OREGON	TER RESOURCES DEPT	
(1) OWNER: Name Duglas Hordon	(10) LOCATION OF WELL: County Driller's well no	SALEM, OREGON	
seemed by Bod 12A Banks Oil	NN 14 NW 14 Section 34 T. 21	R. 4W W.M.	
Address Rt Box 62A Banks Orl 97166	Bearing and distance from section or subdivisi		
(2) TYPE OF WORK (check):	Dearing and distance from section of subdivision corner		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) YEAR PROPERTY CONTRACTOR	-11	
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 220 ft.		
Rotary Driven Domestic D Industrial Municipal Cable Deficient	Static level 85 ft. below land a	surface. Date 4-2.7-81)	
Dug 🖸 Bored 🖸 Irrigation 🗹 Test Well 🗍 Other 📋	Artesian pressure lbs. per squar	e inch. Date	
(5) CASING INSTALLED: Threaded Welded Threaded Welded Threaded Thre	(12) WELL LOG: Diameter of well below casing		
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strats.		
(6) PERFORATIONS: Perforated? Pyes No.			
Type of perforator used Joseph	MATERIAL	From To SWL	
Size of perforations 4 in. by in.	Brown Rail		
72 perforations from 220 ft. to 280 ft.	Bro clay	20 70	
perforations from ft. to ft.	Orn sandstone	70 200	
perforations from ft. to ft.	Pan pa-d clone - layers		
(7) SCREENS: Well screen installed? Yes Wo	Rock + granel	200 285 85	
Manufacturer's Name		1.21.	
Type Model No			
Diam. Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.		4	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	¥ - 44 * 4		
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	To the Name of the	12793	
Yield: gal./min. with ft. drawdown after hrs.	The second and the second	711	
	Fermie IVO.		
Baller test (D gal/min. with /00 ft. drawdown after 2 hrs.		A hard	
Artesian Gos		Market and the second of the s	
	40	ed 4-23 1980	
Temperature of water Depth artesian flow encountered ft.			
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-23 1950	
Well seal-Material used Cernini	Drilling Machine Operator's Certification:	*	
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of seal in.	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Joseph Just Date 4-23, 1980		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator) Drilling Machine Operator's License No.		
How was cement grout placed?	Drining Machine Operator's Encense 140.		
Vienteo	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
	true to the best of my knowledge and belief.		
Was a drive shoe used? Yes Yoo Plugs Size: locationft.	Name Dus Journalis Pell Arilling		
Did any strata contain unusable water?	(Person, firm or corporation) (Type or print) (
Type of water? depth of strata	Address 2007338 Warner		
Method of sealing strata off	[Signed] Joseph Sus	sel	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	TACTOR)	
	I Continue to the Continue of	- 7 - AL .J +0/2()	