

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED APR 9 1969

RECEIVED WATER WELL REPORT APR 15 1969

WASH 5374 IN/2W-15

STATE OF OREGON

State Well No.

(Please type or print)

(Do not write above this line)

State Permit No.

(1) OWNER:

Name Clinton I Nelson Address 5635 SW 145th Beaverton, Ore

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 80'6" ft. Gage 17' 5 9/16" Diam. from 75' ft. to 85' ft. Gage 10'

PERFORATIONS:

Perforated? [X] Yes [] No. Type of perforator used Torch Size of perforations 1/8 in. by 12 in. 3 perforations from 80 ft. to 84 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 20 ft. below land surface Date April-69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Baller test 20 gal./min. with 60 ft. drawdown after 1 hrs. Artesian flow g.p.m. Date

(10) CONSTRUCTION:

Well seal—Material used 200# Portland Depth of seal 18 ft. Diameter of well bore to bottom of seal 10 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Wash Driller's well number 1/4 1/4 Section 15 T. 1 N R. 2 W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing

Depth drilled 85 ft. Depth of completed well 85 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: Brown clay (0-19), Brown sandy clay (19-25), Very sticky clay (25-30), Very sticky clay w/ shell gravel (30-36), Brown clay (36-80), Brown sand (80-85).

Work started 3/27/ 1969 Completed 4/1 1969 Date well drilling machine moved off of well 4/1 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Stanley Mount Date Apr 2, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 216

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Phil Gault (Person, firm or corporation) (Type or print)

Address 145th Ave

[Signed] Phil Gault (Water Well Contractor)

Contractor's License No. 4 Date Apr 2, 1969