NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

## WATEL WELL REPORT

STA E OF OREGON

(Plisse type or print)
(Do not write above this line)

WASH

State Well No. N ZW-17

(1) OWNER:	(10) LOÇATION OF WELL:
Name Lee C. Hodges	County Washington Driller's well number
Address 8+ Box 048C	1/ 1/ Southern 17 m /A/ - 2/1/
- Hillsborg Oregon 9712B	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	o again and the
New Well ☐ Deepening ☐ Reconditioning ☐ Abandc ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (che k):	Depth at which water was first found 178
Rotary Driven Domestic Industrial Munic pal	3.0
Cable	The state of the s
	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
9. Diam. from 0 ft. to 150 ft. Gage 50 5 hb Diam. from 142 ft. to 195 ft. Gage 88	Depth drilled 195 ft. Depth of completed well 195 ft.
	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and noviton named to
PERFORATIONS: Perforated? Pres   No	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Torch	MATERIAL
Size of perforations 1/8 in. by 6 in.	The swift
20 perforations from 175 ft. to 195 ft.	Walland Tank al
perforations fromft. toft.	Blue sandy clay 16 94
perforations from ft. to ft.	Grey sandy clay 94/03
(7) SCREENS: Well screen installed? [] Vos. [] Vos.	Lt/ brown sandy clay 103 121
(1) SCREENS: Well screen installed? ☐ Yes ☐ No Manufacturer's Name	Blue sandy clay / 121 176
Type	Brown sand + pela grave 176 195
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is	
lowered below static level	MLULIALD
Was a pump test made? Yes No If yes, by whom?	AUG271973
Yield: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " " "	WATER RESOURCES DEPT.
7.1	CALC'A OPEGON
Batter test 25 gal./min. with 155ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 9-11 1070 11 8 / 76
	Date well dellies and the second
(9) CONSTRUCTION: Well seal-Material used <u>cement + 5% Bent</u> nite	
Well sepled from land surface to	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface to	Materials used and information reported above are true to my
Diameter of well bore below seal	best knowledge and belief.
Number of sacks of cement used in well seal /3 acks	[Signed] War Featur Date 8-20, 1979
How was cement grout placed?pumped	Drilling Machine Operator's License No. 1217
	A CONTRACT OF THE PROPERTY OF
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?  Yes Ao Plugs Size: location ft.	Name Mrner Drilling Co. Inc.
Old any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address/17/ Box 522 tortland, Ore. 9723
Method of sealing strata off	[Signed] Wan Fraken
Was well gravel packed? Tyes No Size of gravel:	Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 715 Date 8-20 , 1979
(USE ADDITION IL SH	EETS IF NECESSARY)