WASH 53776

JUL 27 1998

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765)

WATER RESOURCES DEPT. SALEM, OREGON

WBLL I.D. # L	18412	
STADT CARD #	115063	

Instructions for completing this report are on the last page of this form.			
1) OWNER: Well Number 516	(9) LOCATION OF WELL by legal descript		
Name Henry Roshak	Township 2S N or S Range	1W E or W. WM.	
Address 7120 SW 125th Pl.	Section 7 NE 1/4	NE 1/4	
City Beaverton State OR Zip 97008	Tax Lot 3110 Lot Block		
2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonment	Street Address of Well (or nearest address) B1	ull Mountain Rd	
3) DRILLMETHOD:			
	(10) STATIC WATER LEVEL: 170 ft. below land surface.	Date 7/1/98	
Other 4) PROPOSED USE:	Artesian pressure Ib. per square in	nch. Date	
PROPOSED USE: Domestic	(11) WATER BEARING ZONES:		
Thermal Injection Livestock Other	, ,		
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found 140		
Special Construction approval Yes No Depth of Completed Well 380h.			
Explosives used Yes No Type Amount From		Estimated Flow Rate SWL	
HOLE SEAL	<u> </u>	170	
Diameter From To Material From To Sacks or pounds	270 280	10 170	
10" 0 25 Bentonite 0 6 3 Sacks	340 370	69 170	
8" 25 39 Cement 6 39 9 Sacks			
6" 39 380			
	(12) WELL LOG:		
How was seal placed: Method □A ☑B □C □D □E	Ground Elevation		
Other		- - -	
Backfill placed from ft. to ft. Material	Material	From To SWL	
Gravel placed from ft. to ft. Size of gravel	Clay - Brown	0 19	
(6) CASING/LINER:	Basalt - Brown - Soft	10 15	
Diameter From To Gauge Steel Plastic Welded Threaded	Basalt - Gray & Brown	15 100	
Casing: 6" +2 38 1/4 🔀 🔲 🖼 🔲	Basalt - Gray & Brown	100 125	
	Decomposed Place	100 125 125 140	
	Basalt - Gray & Black	123 1130	
Liner: 4" 0 380	Basalt - Red & Brown	140 160 170	
	Decomposed Basalt - Brown & Black	140 100 170	
		160 175	
Final location of shoe(s)	Basalt - Brown & Gray	100 175	
(7) PERFORATIONS/SCREENS: Perforations Method Drilled 1" holes	Broken	175 215	
Perforations Method Drilled I" holes	Basalt - Gray&Black-Hard	215 240	
Shu Tele/sine	Basalt - Brown - Soft	24 0 280 170	
From To size Number Diameter size Casing Liner	Basalt - Gray & Brown	280 340	
360 380 1"his 45 4	Basalt - Red&Gray-Broken	340 370 170	
	Basalt - Brown&Gray-Broken	370 378	
	Basalt - Gray	378 380	
(8) WELL TESTS: Minimum testing time is 1 hour	Date started 7/1/98 Complete		
Flowing	(unbonded) Water Well Constructor Certification		
- I greated the work I performed on the construction, alteration of at		ction, alteration, or abandonment	
Pump Bailer Aresian Yield gal/min Drawdewn Drill stem at Time Materials used and information reported above are true to the best of my kno		rue to the best of my knowledge	
69 1 hr.	and belief.		
	WWC Number		
	Signed	Date	
Temperature of water 56 Depth Artesian Flow Found (bonded) Water Well Constructor Certification:			
Was a water analysis done? Yes By whom I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work			
Did any strata contain water not suitable for interacted user for since performed during this time is in compilative with original water and belief. Salty Muddy Odor Colored Other Position Colored WWC Number 663 WWC			
Depth of strata:	Simal Kally Call	Date 7/9/98	
	I Signed // T//WVI - 1 / T///	— Desp., _, _,	