NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report are to be filed with the	ELL REPORT WASH  5.508 State Well No. //	1/26	21A - 唐
STATE ENGINEER, SALEM, OREGON 97310 NOV 7 1966 STATE ( within 30 days from the date of well completion.	OF OREGON	•	
(1) OWNER: OREGON	(11) WELL TESTS: Drawdown is amount	water lev	el is
wameMr. H.R.Wittenhagen	lowered below static	evel	<del></del>
AddressRt. 1 Box 60H Hillsboro Ore.	Was a pump test made? ☐ Yes ☐ No If yes, by who Yield: gal./min. with ft. drawdo		
144000	Yield: gal./min. with ft. drawdo	wn alter	hrs.
(2) LOCATION OF WELL:	" " "		"
	Bailer test 12 gal./min. with 73 ft. drawd	lown after	9 hrs.
County Wash. Driller's well number	Artesian flow NO g.p.m. Date	IOWII BILLI	
34 34 Section 16 T. ] N R. 2 W W.M.	Temperature of water Was a chemical analysis	made? 🖂	Yes #1 No
Bearing and distance from section or subdivision corner	(19) WELL LOC.	611	70 -11
		asing	***************************************
	Depth drilled 134 ft. Depth of completed w		
	Formation: Describe by color, character, size of materishow thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	al and stru the mater change of	cture, and ial in each formation.
(3) TYPE OF WORK (check):	MATERIAL	FROM	то
#	Top Soil	0	11/2
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ andonment, describe material and procedure in Item 12.	Dun DOTT	13	3
	Hard pan	3	12
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Brown sand and br.clay	12	23
Domestic   Industrial   Municipal   Rotary   Driven	Cemented Blue sand	23	<b>2</b> 9
rrigation # Test Well   Other   Cable # Jetted   Stock Watering Dug   Bored	Fine blue sand& soft Blue of	+ 60	9 53
(A) CACTATO VACORATE TO	Hard blue clay	53	54_
	Very thin layers sd.&clay	154	61*
6" Diam from Plus 6t" to 124 ft. Gage 17#	Yellow clay	61 <del> </del>	<del>*#67</del>
9/16." odm. from 122 ft. to 134 ft. Gage 10	Brown clay	67	<del>76</del>
	1 ACTA TITLE DIOMIT BETTO	76	<del>79</del>
(7) PERFORATIONS: Liner Perforated Perforated? Yes No	Hard brown clay	99	99
Type of perforator used Torch	Hard blue clay	123	107
Size of perforations 1/8 By 1rp by 12 in.	Layers clay and sand very f	ine	<del>-161</del>
perforations from 124 ft. to 134 ft.		127	728
2 3 by Increasions from 130 ft. to 134 ft.	Blue clay =	73/	
ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ☐ No	B		
Manufacturer's Name			
YneModel No.		1	
Slot size Set from ft. to ft.	Work started Oct. 2519 Completed 1	7 2 6	6
Diam Slot size Set from ft. to ft.		1-2-6	
9) CONSTRUCTION:		3-66	19
	(13) PUMP:		
Well seal—Material used in seal Bentonite	Manufacturer's Name	***************************************	Mortagonogana paga.
Depth of seal 23 ft. Was a packer used? NO	Type:		
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:		
Were any loose strata cemented off? Tyes Tho Depth			
Was a drive shoe used#□ Yes □ No 6" COUPLING  Was well gravel packed? □ Yes #□ No Size of gravel:	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Was well gravel packed? ☐ Yes ᡮ No Size of gravel:	` <b>!</b>		
,,	NAME Lee Barton Well Drillir (Person, firm or corporation) (T	ype or print	······································
Did any strata contain unusable water? 🔲 Yes 🛱 No	(1)		
Type of water?	Address 25805 N.W. Evergreen st		
Type of water? depth of strata	Address 25805 N.W. Evergreen st	•••••	***************************************
Type of water? depth of strata  Method of sealing strata off  10) WATER LEVELS:	Drilling Machine Operator's License No2	•••••	***************************************
Method of sealing strata off  10) WATER LEVELS:	Drilling Machine Operator's License No		-
Method of sealing strata off	Drilling Machine Operator's License No		-