

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report shall be filed with

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

STATE ENGINEER SALEM OREGON

OBSERVATION WELL

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED WASH 6178 WASH 6178

NOV 15 1968

State Well No. 1N/300-18R(2)

State Permit No. G 5496

Well # 2

(1) OWNER:

Name Sunset Grove Golf Club
Address Rte 2 Box 406 Forest Grove, Ore.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [] Test Well [] Other [X]

CASING INSTALLED:

Threaded [] Welded [X]

6" Diam. from 0 ft. to 260 ft. Gage 1/4 wall

PERFORATIONS:

Perforated [X] Yes [] No []

Size of perforations 1/8 in. by 6 in.
220 perforations from 40 ft. to 260 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 20 ft. below land surface Date 10-29-68
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No
If yes, by whom?
d: gal./min. with ft. drawdown after hrs.
Bailer test 100 gal./min. with 200 ft. drawdown after 1 hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used Bentonite
Depth of seal 25 feet ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? [] Yes [X] No Depth
Was a drive shoe used? [] Yes [X] No
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [X] Yes [] No Size of gravel: 1/2" pea
Gravel placed from 25 ft. to 260 ft. gravel

(11) LOCATION OF WELL:

County Washington Driller's well number
1/4 1/4 Section 18-19 T. 1-N R. 3-W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 6 inch

Depth drilled 260 ft. Depth of completed well 260 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil, Yellow clay, Blue sandy clay, Blue clay, Blue sand, gravel, clay, and wood, Blue clay.

Work started 10-29-68 Completed 10-29-68 19
Date well drilling machine moved off of well 10-29-68 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ralph Turner Date 11-7, 1968
(Drilling Machine Operator)

Drilling Machine Operator's License No. 254

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Ralph Turner Drilling Co.
(Person, firm or corporation) (Type or print)

Address Rte 1 Box 141 Hillsboro, Oregon

[Signed] Ralph Turner
(Water Well Contractor)

Contractor's License No. 247 Date 11-7, 1968