RECE WASH 62488

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765)

JUN 3 0 2005

WATER RESOURCES DEPT Instructions for completing this report are on the 協文印象。 **①种医企**识中

| A | | | |
|--------|---------------|--------|--------|
| reft | WELL I.D. # L | 75348 | \sim |
| WHO IS | | | |
| 12488 | START CARD# | 173599 | |
| por | - | | |

| (1) LAND OWNER Name Oregon Dept. of Forestry, NW Regional Office | (9) LOCATION OF WELL (legal description) © ounty Washington | | | |
|---|---|--|--|--|
| Address 801 Gales Creek Rd. | Tax Lot Lot | | | |
| City Forest Grovetate OR Zip 97116 | Township 3N Nor S Range 5W E or W WM Section 32 NE 1/4 NW 1/4 | | | |
| (2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonment Conversion | Section32 NE | | | |
| (3) DRILL METHOD ☑ Rotary Air ☐ Rotary Mud ☐ Cable ☐ Auger ☐ Cable Mud ☐ Other | Street Address of Well (or nearest address) Reehers Camp Ground Cochran Rd., Timber, OR | | | |
| (4) PROPOSED USE ☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation ☐ Thermal ☐ Injection ☐ Livestock ☐ Other | (10) STATIC WATER LEVEL 7 | | | |
| (5) BORE HOLE CONSTRUCTION Special Construction: Yes No Depth of Completed Well 20 ft. Explosives used: Yes No Type Amount | Artesian pressure lb. per square inch Date (11) WATER BEARING ZONES | | | |
| BORE HOLE SEAL Diameter From To Material From To Sacks or Pounds 12 0 60 Cem/Bent 0 10 3 sks Bent Chips 10 13 2 sks | Depth at which water was first found 8'/13' From To Estimated Flow Rate SWL 13 15 2-3 gpm 7' | | | |
| Cem/Bent 18 60 16 sks 6 60 440 See #12 | | | | |
| How was seal placed: Method A B C D E Other Bentonite chips poured slowly into annu Backfill placed from 13 ft. to 18 ft. Material Motor Gravel placed from 13 ft. to 18 ft. Size of gravel Post Classification. | Brn.clay w/gravel/cobbles 0 8 Brn.gravel/cobble w/clay 8 13 7 | | | |
| (6) CASING/LINER Diameter From To Gauge Steel Plastic Welded Threaded Casing: 6" +1 61 .250 | Gray-brn.gravel, some clay 13 15 7 Orange-brown clay 15 18 Gray clay/claystone, 18 Occ. gray-brown claystone qummy sticky, occ. hard streaks. NO WATER/DRY 440 Lower bore hole Abandonment: Casing perforated for abandonment (20-60') High solids bentonite grout & cement graut plug 440-60 (23 sks) | | | |
| (7) PERFORATIONS/SCREENS | Cement grout 60-20 (5 sks) | | | |
| ☑ Perforations Method Air Rotary ☐ Screens Type | Date Started 06/07/2005 Completed 06/28/2005 | | | |
| From To Slot Number Diameter Tele/pipe Casing Liner | (unbonded) Water Well Constructor Certification I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief. WWC Number Date | | | |
| (8) WELL TESTS: Minimum testing time is 1 hour → Pump ☐ Bailer ☒ Air ☐ Flowing Artesian | Signed | | | |
| Yield gal/min Drawdown Drill stem at 1 hr. 11-2 16 1 hr. 11-2 24 hrs. At throa | (bonded) Water Well Constructor Certification I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief. WWC Number 573 Date 06/28/2005 | | | |
| ORIGINAL – WATER RESOURCES DEPARTMENT FIRST COPY – CONSTRUCTOR SECOND COPY – CUSTOMER 06/16/20 | | | | |

WATER RESOURCES DEPT SALEM, OREGON



June 17, 2005

Water Resources Department North Mall Office Building 725 Summer Street NE, Suite A Salem, OR 97301-1266 503-986-0900 FAX 503-986-0904

A M JANNSEN DRILLING PRESTON A. JANNSEN #573 21075 SW T. V. HWY ALOHA OR 97006

Dear Preston:

The Special Standard request you submitted for owner: Oregon Department of Forestry, Start Card number 173599 is hereby approved for the following: You may complete this well to 20 feet bgs with a 13 foot annular seal. The casing shall have perforations from 13 feet bgs to 20 feet bgs to allow water to enter the well. Gravel may be placed in the annular space from 13 feet bgs to 18 feet bgs. The casing and borehole from 20 feet bgs to 440 feet bgs shall be properly abandoned with cement grout per OAR 690-220-0060. All other construction requirements apply. See Oregon Administrative Rule 690-210-0140. Your Special Standard request form is enclosed.

The Well Construction Standards serve to protect ground water resources. By approving and issuing this special construction standard the Oregon Water Resources Department is not representing that a well constructed in accordance with this condition will maintain structural integrity or that it meets engineering standards. The well constructor/or landowner is responsible for ensuring that a well is constructed in a manner that protects ground water resources as required under Oregon Administrative Rules 690-200 through 690-240.

If you have any questions concerning this letter, please contact me at (503) 986-0851, or by e-mail at Kristopher.R.Byrd@wrd.state.or.us.

Sincerely,

Kristopher Byrd / Vell Construction Program Coordinator

Enforcement Section

enclosure

cc:

Joel Jeffery, NW Region Well Inspector

File

This is a final order in other than contested case. This order is subject to judicial review under ORS 183.484. Any petition for judicial review must be filed within the 60 day time period specified by ORS 183.484(2). Pursuant to ORS 536.075 and OAR 137-004-0080 you may either petition for judicial review or petition the Director for reconsideration of this order. A petition for reconsideration may be granted or denied by the Director, and if no action is taken within 60 days following the date the petition was filed, the petition shall be deemed denied.

PEVED

JUN 3 0 2005

WATER RESOURCES DEPT SALEM, OREGON