NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 PSH within 30 days from the date of well completion.

WATER WELL REPRECEIVED

STATE OF OREGON

State Well No.

(Please type or print) (Do not write above this light ENGINEER State Permit No. ..

| <i> N</i> | 1/3 | -25 |
|-----------|-----|-----|
| | | |

| | CALCIA OBECOM | | |
|--|--|--|--|
| (1) OWNER: | (10) LOCATION OF WELL: | | |
| Name Columbia Pacific Council-Boy Scouts of | County Washington Driller's well number | | |
| Address 2145 S.W. Front Avenue America | 1/4 1/4 Section 25 T. 1 N R. 3 W. W.M. | | |
| Portland, Oregon | Bearing and distance from section or subdivision corner | | |
| (2) TYPE OF WORK (check): | | | |
| New Well 🚨 Deepening 🗌 Reconditioning 🗍 Abandon 🗍 | AND THE PROPERTY OF THE PROPER | | |
| If abandonment, describe material and procedure in Item 12. | (11) WATER LEVEL: Completed well. | | |
| (3) TYPE OF WELL: (4) PROPOSED USE (check): | Depth at which water was first found 54 ft. | | |
| Rotary Driven Domestic Maintenant Municipal Domestic Maintenant Domestic Maintenant Domestic Maintenant Domestic Domestic Maintenant Domestic Domes | Static level 15 ft. below land surface. Date 5/7/74 | | |
| Cable | Artesian pressure lbs. per square inch. Date | | |
| CASING INSTALLED: Threaded □ Welded □ | (12) WELL LOG: Diameter of well below casing 6" | | |
| Diam. from + 1011 X to 461911 ft. Gage 250 | Depth drilled 60 ft. Depth of completed well 60 ft. | | |
| 5-9/16" Diam from 40 ft. to 60 ft. Gage •188 | Depart drined 00 It. Depart of completed went 1t. | | |
| ft. toft. Gage | Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, | | |
| PERFORATIONS: Perforated? TVes No | with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. | | |
| manustration (2010) | | | |
| 7/0 70 | Topsoil From To SWL | | |
| | Soft brown silty clay 2 31 | | |
| - | Soft gray clay w/some sand | | |
| perforations fromft. toft. | particles 31 54 | | |
| perforations from ft. to ft. | Soft gray silty clay 54 60 | | |
| (7) SCREENS: Well screen installed? Yes No | | | |
| Manufacturer's Name | . *2 | | |
| Type Model No. | T | | |
| Diam Slot size Set from ft. to ft. | , | | |
| Diam. Slot size Set from ft. to ft. | | | |
| (8) WELL TESTS: Drawdown is amount water level is | | | |
| lowered below static level | | | |
| Was a pump test made? ☐ Yes ☐ No If yes, by whom? | | | |
| Yield: gal./min. with ft. drawdown after hrs. | | | |
| у н н | | | |
| " " " " " | | | |
| Bailer test 3 gal./min. with 22 ft, drawdown after 2 hrs. | part of the control o | | |
| Artesian flow g.p.m. | | | |
| nperature of water Depth artesian flow encountered ft. | Work started 5/2/74 19 Completed 5/7/74 19 | | |
| (9) CONSTRUCTION: | Date well drilling machine moved off of well 5/7/74 19 | | |
| Well seal—Material usedBentonite | Drilling Machine Operator's Certification: | | |
| Well sealed from land surface toft. | This well was constructed under my direct supervision. Materials used and information reported above are true to my | | |
| Diameter of well bore to bottom of seal in. | best knowledge and belief | | |
| Diameter of well bore below sealin. | [Signed] Date5/8/74, 19 | | |
| Number of sacks of cement used in well seal | Drilling Machine Operator's License No. 751 | | |
| Number of sacks of bentonite used in well seal sacks Brand name of bentonite | The state of the s | | |
| | Water Well Contractor's Certification: | | |
| Number of pounds of bentonite per 100 gallons of water lbs./100 gals. | This well was drilled under my jurisdiction and this report is | | |
| Was a drive shoe used? Wes No Plugs Size: location ft. | true to the best of my knowledge and belief. | | |
| Did any strata contain unusable water? Yes M No | Name A. M. Jannsen Drilling Co. (Person, firm or corporation) (Type or print) | | |
| Type of water? depth of strata | Address 21075 8 W. Tualatin Valley Hwy. | | |
| Method of sealing strata off | The of the sale | | |
| Was well gravel packed? ☐ Yes ☒ No Size of gravel: | [Signe (Water Well Contractor) | | |
| | % E/8/71. | | |
| Gravel placed from ft. to ft. | Contractor's License No. 17 Date 2/0/14, 19 | | |