## **WASH 64120**

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

WELL LABEL # L	84439
START CARD#	187476

(1) LAND OWNER Owner Well I.D.	(9) LOCATION OF WELL (legal description	(on)	
(1)	County WASHINGT Two 1 S N/S Rang		
First Name Last Name Company Eshraghi Nursery	1	x Lot 1401	
Address 26985 SW Farmington Rd.	Tax Map Number Lot		
City Hillsboro State OR Zip 97123	Lat °0 ' "or	DMS or DD	
	Long ° 0 ' " or	DMS or DD	
(2) TYPE OF WORK New Well Deepening Conversion  Alteration (repair/recondition) Abandonment	Street address of well Nearest address	ess	
(3) DRILL METHOD	26985 SW Farmington Rd.		
Rotary Air   Rotary Mud   Cable   Auger   Cable Mud   Reverse Rotary   Other   Cable   Cable Mud   Cable Mud   Cable   Cable Mud   Cable Mud   Cable   Cable Mud   Cable Mud	(10) STATIC WATER LEVEL Date SWL(	(psi) + SWL(ft)	
(4) PROPOSED USE Domestic XIrrigation Community	Existing Well / Predeepening		
Industrial/Commercial Livestock Dewatering	Completed Well 06-16-2006	14	
Thermal Injection Other	Flowing Artesian?	<del></del>	
	WATER BEARING ZONES Depth water was fir		
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy)	SWL Date From To Est Flow SV 06-15-2006 450 518 250	VL(psi) + SWL(fit)	
Depth of Completed Well 532 ft.  BORE HOLE SEAL sacks/			
Dia From To Material From To Amt lbs			
13 0 448 Cement 0 90 46 S			
Cement 390 448 35 S			
8 448 532 (11) WELL LOG Ground Elevation			
How was seal placed: Method A B B C D E	TVILLET REL	rom To	
Other	Fill	0 1 19	
Backfill placed from 90 ft. to 390 ft. Material Bent, Drill Slurry	Brown clay Gray silty clay	19 69	
Filter pack from ft. to ft. Material Size /	Fine to medium black sand	69 83	
Explosives used: Yes Type Amount	Sticky brown clay	83 142	
(6) CASING/LINER	Sticky gray clay	142 168	
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	Sticky brown clay	168 184	
	Sticky red-brown clay occ. decomp. basalt streaks Sticky brown clay	184 239 239 247	
	Sticky gray clay	247 349	
	Soft gray-brown clay	349 391	
	Decomp. brown basalt	391 428	
	Hard gray-black basalt	428 488 488 503	
Shoe Inside Outside Other Location of shoe(s)	Firm gray-brown basalt, occ. fractured Soft brown visicular basalt	503 505	
Temp casing Yes Dia From To	Firm gray-brown basalt w/soft brown interbeds	505 518	
7) PERFORATIONS/SCREENS Hard gray basalt		518 532	
Perforations Method			
Screens Type Material Perf/ Casing/Screen Servision Slot # of Tele/ Date Started or 02 2006			
Perf/ Casing/Screen Sern/slot Slot # of Tele/ Screen Liner Dia From To width length slots pipe size  Date Started 06-02-2006  Completed 06-16-2006			
	(unbonded) Water Well Constructor Certification	1 1 1	
	I certify that the work I performed on the construction abandonment of this well is in compliance with O		
	construction standards. Materials used and information		
	the best of my knowledge and belief.	•	
(8) WELL TESTS: Minimum testing time is 1 hour	License Number Date		
Pump Bailer • Air Flowing Artesian	Password : (if filing electronically)		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) 150 200 I			
200 400	(bonded) Water Well Constructor Certification	alternation of the state of	
250 525	I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work		
Temperature 57 °F Lab analysis Yes By RECEIVED	performed during this time is in compliance with Oregon water supply well		
Water quality concerns? Yes (describe below)	construction standards. This report is true to the best of my knowledge and belief.		
From To Description JUNA-Boutht 2006	License Number 1266 Date 06-19-2006		
	Password (if filing electronically)		
WATER RESOURCES DEF			
SALEW, UMEGON	Contact Info (optional)		